

No. 1907/2006 (REACH) Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Easy-Mix PE-PP 45 Resin

Code-Nr. 106601

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

> Phone : +49(0)251 / 9322 - 0 Fax: +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Skin Sens. 1 H317 H360D Repr. 1B **Aquatic Chronic 3** H412

Hazard Statements

May cause an allergic skin reaction. H317 H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS07

GHS08

! Signal word

Danger

Hazard Statements

H317 May cause an allergic skin reaction. H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P201 P260 P264 P272 P273	Obtain special instructions before use. Do not breathe vapours/spray. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.
P302 + P352 P308 + P313 P312 P333 + P313 P363	IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

2-[(2-methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate, 2-ethylhexyl methacrylate, Tetrahydrofurfuryl methacrylate

Supplemental Hazard information (EU)

Corrosive to the respiratory tract.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
80-62-6	201-297-1	methyl methacrylate	< 0,3	Flam. Liq. 2, H225 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Skin Sens. 1, H317



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	< 0,3	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317	
688-84-6	211-708-6	2-ethylhexyl methacrylate	10 - 24	Skin Sens. 1B, H317 / Aquatic Chronic 3, H412	
21282-97-3	244-311-1	Butansäure, 3-oxo-, 2-[(2-methyl-1-oxo-2- propenyl)oxo]ethylester	1 - 15		
93924-19-7	300-212-6	Aschen (Rückstände), Cenospheren	1 - 5		
108-30-5	203-570-0	succinic-anhydride	0,1 < 0,7	Acute Tox. 4, H302 / Skin Corr. 1, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Resp. Sens. 1, H334 / , EUH071	
2455-24-5	219-529-5	Tetrahydrofurfuryl methacrylate	30 - 70	Skin Sens. 1, H317 / Repr. 1B, H360D / Aquatic Chronic 3, H412	
20882-04-6	244-096-4	2-[(2-methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	1 - 9	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317	
REACH					
CAS No	Name			REACH registration number	
80-62-6	methyl metha	acrylate		01-2119452498-28	
868-77-9	2-hydroxyeth	yl methacrylate	01-2119490169-29		
688-84-6	2-ethylhexyl	methacrylate	01-2119490166-35		
21282-97-3	Butansäure,	3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxo]ethylester		01-2119970348-28	
93924-19-7	Aschen (Rüc	kstände), Cenospheren		01-2119563688-21	
108-30-5	succinic-anh	ydride		01-2119485841-30	
2455-24-5	•	furyl methacrylate	01-2120748481-53		
20882-04-6	2-[(2-methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate 01-2120137902-58				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

vomiting

Respiratory complaints

Nausea

Confusion

skin irritation



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

Hydrogen cyanide (HCN)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust). After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8



No. 1907/2006 (REACH) Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

Cloths contaminated with product should not be kept in trouser pockets.

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store with acids.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Store only in original container at cool and aired place.

Protect from direct solar radiation.

Protect from heat/overheating.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1333-86-4	Carbon black	8 hours Short-term	3.5 7		EH40/2005
80-62-6	Methyl methacrylate	8 hours Short-term	208 416	50 100	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
80-62-6	methyl-methacrylate	8 hours		50	
		Short-term		100	
DNEL-/PNE DNEL work					
CAS No	Substance name	Value	Code	F	Remark
868-77-9	2-hydroxyethyl methacrylate	4,9 mg/m3	DNEL long-term inhalative (systemic)		



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

DNEL-/PNEC-values (continued)						
CAS No	Substance name	Value	Code	Remark		
		1,3 mg/kg bw/day	DNEL long-term dermal (systemic)			
PNEC						
CAS No	Substance name	Value	Code	Remark		
868-77-9	2-hydroxyethyl methacrylate	3,79 mg/kg	PNEC soil, freshwater			
		10 mg/l	PNEC sewage treatment plant (STP)		

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter A2/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

liquid black typical, pungent

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	> 82,2 °C				
melting point	not applicable				
Flash point	103,3 °C			closed cup	



No. 1907/2006 (REACH) Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

	Value	Temperature	at	Method	Remark
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	not determined				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 13,3 Pa	20 °C			
Relative density	ca. 0,98 g/ml	20 °C			
Vapour density	not determined				
Solubility in water					easy soluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	25 Pa*s				
Oxidising properties No information available.					
Explosive properties no					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

Light effect.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

10.5. Incompatible materials Substances to avoid

Acid, concentrated Oxidising agent, strong

10.6. Hazardous decomposition products

Gases/vapours, toxic Hydrogen cyanide (hydrocyanic acid) Carbon monoxide and carbon dioxide. Nitrous oxides (NOx) Aldehydes

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg			ATE
LD50 acute dermal	> 2000 mg/kg			ATE
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity				-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity	NOAEL (F1) 120 mg/kg	Rat		Indications of toxic effects are available from reproduction studies in animals.
	CAS: 2455-24-5			iii aiiiiiais.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Experiences made from practice

Swallowing may cause vomiting and diarrhoea.

May irritate the mucosae.

Risk of strong health injuries in case of long-term exposition.

Sensitization through skin contact possible.



No. 1907/2006 (REACH) Printed

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

Irritates respiratory tract.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation	
Fish	LC50 34,7 mg/l (96 h)	Pimephales pro	omelas	CAS: 2455-24-5	
Daphnia	EC50 4,6 mg/l (48 h)	Daphnia magna	a	CAS: 688-84-6	
Algae	EC50 5,3 mg/l (72 h)	Green algae		CAS: 688-84-6	
12.2. Persiste	nce and degradability Elimination rate	Method of analysis	Method	Validation	
Biological	88 % (28 d)		OECD 301 C	Biodegradable	
degradability	CAC: 600 04 6				

CAS: 688-84-6

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No. Name of waste

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous

substances

20 01 27* paint, inks, adhesives and resins containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	; -	-	-

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 1 % VOC value ca.10 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 08.04.2019 (GB) Version 9.0

Easy-Mix PE-PP 45 Resin

EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H360D	May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H412	Harmful to aquatic life with long lasting effects.