

Datasheet

Stock No:1707008

# RS Pro SSMA 2 HOLE FLANGE JACK (EXPOSED TEFLON)

<b>NO</b>	<b>DESCRIPTION</b>	<b>DATE</b>
△	WORKING VOLTAGE → VOLTAGE RATING DEL PRDIF VOLTAGE	01.31.13'
△	49-08/H49-008-00-0032210LL → 40490208500003	02.01.18'

  
  

APPROVED by \_\_\_\_\_ DATE: \_\_\_\_\_

  

<b>DESCRIPTION</b> SSMA 2 HOLE FLANGE JACK (EXPOSED TEFLON)		<b>品名</b> 40490208500003	<b>日</b> 04.19.07'	<b>版</b> A-2
<b>製圖</b> Jackie	<b>TOLERANCE</b> ±0.2	<b>品名</b> (500)	<b>REV.</b>	
<b>檢圖</b> Arc	XX ±0.1	<b>UNIT</b> mm(in)	<b>ROHS COMPLIANT</b>	
<b>認圖</b> Jenny	XXX ±0.05	<b>SCALE</b>	<b>DWG. NO.</b> 49-0008-Z	
<b>定</b>	<b>ANGLE</b> ±5°	<b>比例</b> 6:1		

  

<b>3</b>	INSULATION	TEFLON	1	NONE
<b>2</b>	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 50μ MIN.
<b>1</b>	BODY	STAINLESS STEEL	1	GOLD 3μ MIN.
<b>NO DESCRIPTION</b>	<b>MATERIAL</b>		<b>QTY</b>	<b>FINISH</b>

  

**1.0 ELECTRICAL**

1.1 FREQUENCY RANGE: DC-38 GHz  
 1.2 NOMINAL IMPEDANCE: 50 OHM  
 1.3 VOLTAGE RATING: 250 VOLTS MAX. △  
 1.4 VSWR: 1.3 MAX. @18 GHz

**2.0 MATERIALS**

2.1 BODIES: STAINLESS STEEL PER AISI 303  
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B186 UNS C17300  
 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

**3.0 FINISHES AND OTHERS**

3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A

**5.0 ENVIRONMENTAL**

5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C