

# Metal Oxide Film Resistors - Axial Leaded

**multicomp** PRO

**RoHS  
Compliant**




## Features

- Excellent Long-Time stability
- High surge / overload capability
- Controlled temperature coefficient
- Resistance standard tolerance:  $\pm 2\%$  and  $\pm 5\%$
- Electrical and mechanical stability and high reliability

## Applications

- Telecommunication
- Medical Equipment




1	Ceramic Rod	4	Non-flame Paint With Sol Vent-proof
2	Tinned Iron Caps	5	Colour Code
3	Metal Oxide Film	6	Lead Wire


## Dimensions

L	D	H	D	Weight (g) (1000pcs)
11.5 $\pm$ 1.0	4.5 $\pm$ 0.5	35 $\pm$ 2.0	0.78 $\pm$ 0.03	760

## Derating Curve



## Hot-Spot Temperature



Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
Element14.com/multicomp-pro

**multicomp** PRO

# Metal Oxide Film Resistors - Axial Leaded

**multicomp** PRO

## Standard Electrical Specifications

Item Type	Power Rating at 70°C	Operating Temp. Range	Max. Operating Voltage	Max. Overload Voltage	Dielectric Withstanding Voltage	Resistance Range		TCR (PPM/°C)
						±2%	±5%	
1145	1W	-55°C to +235°C	500V	600V	500V	10Ω to 9.1MΩ	1Ω to 3Ω	±200

Operating Voltage= $\sqrt{P \cdot R}$  or Max. operating voltage listed above, whichever is lower.

Overload Voltage= $2.5 \cdot \sqrt{P \cdot R}$  or Max. overload voltage listed above, whichever is lower.

Resistor body colour: Standard Power Rating: Grey

High Power Rating : Grey or Pink are available

## Environmental Characteristics

Item	Requirement	Test Method
Short Time Overload	$\pm(0.5\%+0.05\Omega)$	IEC-60115-1 4.13 2.5 times RCWV for 5 seconds
Insulation Resistance	>10000MΩ	JIS-C-5202 5.6 In V-Block
Endurance	$\pm(1.5\%+0.05\Omega)$	IEC-60115-1 4.25 70±2°C, RCWV for 1000 hrs with 1.5 hrs "ON" and 0.5 hrs "OFF"
Damp Heat with Load	$\pm(1.5\%+0.05\Omega)$	IEC-60115-1 4.24 40±2°C, 90~95% R.H. RCWV for 1000 hrs with 1.5 hrs "ON" and 0.5 hrs "OFF"
Solderability	95% min. Coverage	IEC-60115-1 4.17 260±5°C for 3±0.5 seconds
Voltage Proof	By Type	IEC-60115-1 4.7 In V-Block for 60 seconds
Temperature Coefficient	By Type	IEC-60115-1 4.8 Resistance value at room temperature and room temperature+125°C
Pulse Overload	$\pm(1\%+0.05\Omega)$	IEC-60115-1 4.39 4 times RCWV for 10000 cycles with 1second "ON" and 25 seconds "OFF"
Resistance To Solvent	No deterioration of coatings and markings	IEC-60115-1 4.30 IPA for 5±0.5 min. with ultrasonic
Terminal Strength	Tensile: ≥ 2.5kg	IEC-60115-1 4.16 Direct Load for 10 seconds In the direction off the terminal leads

RCWV(Rated continuous working voltage)=  $\sqrt{P \cdot R}$  or Max. Operating voltage whichever is lower

Storage Temperature: 15°C to 28°C; Humidity < 80%RH

# Metal Oxide Film Resistors - Axial Leaded

**multicomp** PRO

## Part Number Table

Description	Part Number
Axial Leaded Metal Oxide Film Resistor, 1W, 10R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006406
Axial Leaded Metal Oxide Film Resistor, 1W, 20R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006407
Axial Leaded Metal Oxide Film Resistor, 1W, 100R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006408
Axial Leaded Metal Oxide Film Resistor, 1W, 1K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006409
Axial Leaded Metal Oxide Film Resistor, 1W, 10K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006410
Axial Leaded Metal Oxide Film Resistor, 1W, 100K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006411
Axial Leaded Metal Oxide Film Resistor, 1W, 1M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006412
Axial Leaded Metal Oxide Film Resistor, 1W, 1M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006413
Axial Leaded Metal Oxide Film Resistor, 1W, 110R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006414
Axial Leaded Metal Oxide Film Resistor, 1W, 1.1K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006415
Axial Leaded Metal Oxide Film Resistor, 1W, 11K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006416
Axial Leaded Metal Oxide Film Resistor, 1W, 110K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006417
Axial Leaded Metal Oxide Film Resistor, 1W, 1.1M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006418
Axial Leaded Metal Oxide Film Resistor, 1W, 120R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006419
Axial Leaded Metal Oxide Film Resistor, 1W, 1.2K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006420
Axial Leaded Metal Oxide Film Resistor, 1W, 12K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006421
Axial Leaded Metal Oxide Film Resistor, 1W, 120K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006422
Axial Leaded Metal Oxide Film Resistor, 1W, 150R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006423
Axial Leaded Metal Oxide Film Resistor, 1W, 1.5K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006424
Axial Leaded Metal Oxide Film Resistor, 1W, 15K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006425
Axial Leaded Metal Oxide Film Resistor, 1W, 150K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006426
Axial Leaded Metal Oxide Film Resistor, 1W, 1.5M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006427
Axial Leaded Metal Oxide Film Resistor, 1W, 200R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006428
Axial Leaded Metal Oxide Film Resistor, 1W, 2K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006429
Axial Leaded Metal Oxide Film Resistor, 1W, 20K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006430
Axial Leaded Metal Oxide Film Resistor, 1W, 200K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006431
Axial Leaded Metal Oxide Film Resistor, 1W, 2M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006432
Axial Leaded Metal Oxide Film Resistor, 1W, 220R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006433
Axial Leaded Metal Oxide Film Resistor, 1W, 2.2K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006434
Axial Leaded Metal Oxide Film Resistor, 1W, 22K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006435
Axial Leaded Metal Oxide Film Resistor, 1W, 220K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006436
Axial Leaded Metal Oxide Film Resistor, 1W, 2.2M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006437
Axial Leaded Metal Oxide Film Resistor, 1W, 270R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006438
Axial Leaded Metal Oxide Film Resistor, 1W, 2.7K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006439
Axial Leaded Metal Oxide Film Resistor, 1W, 27K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006440
Axial Leaded Metal Oxide Film Resistor, 1W, 270K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006441
Axial Leaded Metal Oxide Film Resistor, 1W, 2.7M, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006442
Axial Leaded Metal Oxide Film Resistor, 1W, 300R, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006443
Axial Leaded Metal Oxide Film Resistor, 1W, 3K, $\pm 2\%$ , $\pm 200\text{PPM}/^\circ\text{C}$	MP006444

Newark.com/multicomp-pro  
 Farnell.com/multicomp-pro  
 Element14.com/multicomp-pro

**multicomp** PRO

# Metal Oxide Film Resistors - Axial Leaded

**multicomp** PRO

Description	Part Number
Axial Leaded Metal Oxide Film Resistor, 1W, 30K , ± 2%, ± 200PPM/°C	MP006445
Axial Leaded Metal Oxide Film Resistor, 1W, 300K , ± 2%, ± 200PPM/°C	MP006446
Axial Leaded Metal Oxide Film Resistor, 1W, 3M, ± 2%, ± 200PPM/°C	MP006447
Axial Leaded Metal Oxide Film Resistor, 1W, 390R, ± 2%, ± 200PPM/°C	MP006448
Axial Leaded Metal Oxide Film Resistor, 1W, 3.9K , ± 2%, ± 200PPM/°C	MP006449
Axial Leaded Metal Oxide Film Resistor, 1W, 39K , ± 2%, ± 200PPM/°C	MP006450
Axial Leaded Metal Oxide Film Resistor, 1W, 390K , ± 2%, ± 200PPM/°C	MP006451
Axial Leaded Metal Oxide Film Resistor, 1W, 3.9M, ± 2%, ± 200PPM/°C	MP006452
Axial Leaded Metal Oxide Film Resistor, 1W, 470R, ± 2%, ± 200PPM/°C	MP006453
Axial Leaded Metal Oxide Film Resistor, 1W, 470R, ± 2%, ± 200PPM/°C	MP006454
Axial Leaded Metal Oxide Film Resistor, 1W, 4.7K , ± 2%, ± 200PPM/°C	MP006455
Axial Leaded Metal Oxide Film Resistor, 1W, 47K , ± 2%, ± 200PPM/°C	MP006456
Axial Leaded Metal Oxide Film Resistor, 1W, 470K , ± 2%, ± 200PPM/°C	MP006457
Axial Leaded Metal Oxide Film Resistor, 1W, 4.7M, ± 2%, ± 200PPM/°C	MP006458
Axial Leaded Metal Oxide Film Resistor, 1W, 680R, ± 2%, ± 200PPM/°C	MP006459
Axial Leaded Metal Oxide Film Resistor, 1W, 6.8K , ± 2%, ± 200PPM/°C	MP006460
Axial Leaded Metal Oxide Film Resistor, 1W, 68K , ± 2%, ± 200PPM/°C	MP006461
Axial Leaded Metal Oxide Film Resistor, 1W, 680K , ± 2%, ± 200PPM/°C	MP006462
Axial Leaded Metal Oxide Film Resistor, 1W, 6.8M, ± 2%, ± 200PPM/°C	MP006463
Axial Leaded Metal Oxide Film Resistor, 1W, 820R, ± 2%, ± 200PPM/°C	MP006464
Axial Leaded Metal Oxide Film Resistor, 1W, 8.2K , ± 2%, ± 200PPM/°C	MP006465
Axial Leaded Metal Oxide Film Resistor, 1W, 82K , ± 2%, ± 200PPM/°C	MP006466
Axial Leaded Metal Oxide Film Resistor, 1W, 820K , ± 2%, ± 200PPM/°C	MP006467
Axial Leaded Metal Oxide Film Resistor, 1W, 8.2M, ± 2%, ± 200PPM/°C	MP006468
Axial Leaded Metal Oxide Film Resistor, 1W, 910R, ± 2%, ± 200PPM/°C	MP006469
Axial Leaded Metal Oxide Film Resistor, 1W, 9.1K , ± 2%, ± 200PPM/°C	MP006470
Axial Leaded Metal Oxide Film Resistor, 1W, 91K , ± 2%, ± 200PPM/°C	MP006471
Axial Leaded Metal Oxide Film Resistor, 1W, 910K , ± 2%, ± 200PPM/°C	MP006472
Axial Leaded Metal Oxide Film Resistor, 1W, 9.1M, ± 2%, ± 200PPM/°C	MP006473
Axial Leaded Metal Oxide Film Resistor, 1W, 1R, ± 5%, ± 200PPM/°C	MP006474
Axial Leaded Metal Oxide Film Resistor, 1W, 2R, ± 5%, ± 200PPM/°C	MP006475
Axial Leaded Metal Oxide Film Resistor, 1W, 3R, ± 5%, ± 200PPM/°C	MP006476
Axial Leaded Metal Oxide Film Resistor, 1W, 2.2R, ± 5%, ± 200PPM/°C	MP006477

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
 Farnell.com/multicomp-pro  
 Element14.com/multicomp-pro

**multicomp** PRO