

FEATURES

- Threaded hollow cavity inserts
- M5 threading
- Suitable for material thickness range of 0.38 mm to 4.75 mm
- Fixing hole diameter of 10.16 mm
- Flange diameter of 13.49 mm
- Outer body diameter of 9.7 mm
- Body depth of 18.19 mm
- Bright zinc-plated mild steel construction for corrosion resistance

RS PRO Bright Zinc Plated, M5 Steel Threaded Insert, 13.49mm diameter 10.16mm Depth 18.19mm

RS Stock No.: 768-0732



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

For an easy way to create threaded holes in any sheet materials, try this RS PRO threaded insert. They're designed for creating holes for bolts, screws and other fixtures. As the insert is self-adjusting, you'll feel the insert pressing firmly against the sheet when it's fine to stop tightening the screw. Just place the insert and screw into any hole of the accompanying friction wrench. Use these threaded inserts with a range of material thickness from 0.38 mm to 4.75 mm. Just push through pre-drilled holes, and tighten the screw by using the friction wrench until it's flush against the sheet.

General Specifications

Thread Size	M5
Material	Steel
Finish	Bright Zinc Plated
Application	Maintenance of domestic electronics like refrigerators

Mechanical Specifications

Flange Diameter	13.49mm
Fixing Hole Diameter	10.16mm
Body Outside Diameter	9.7mm
Body Depth	18.19mm
Thickness Of Material Maximum	4.75mm
Thickness Of Material Minimum	0.38mm

Approvals

Compliance/Certifications	EN61340
----------------------------------	---------

