Product data sheet Characteristics

XAWF178EX

control station - XAW-F - metal - 1 NC + 1 NC - red - Emergency Stop



Main Range of product Harmony XAW Product or component Complete control station type Device short name XAWF Control station Emergency stop function application Material Metal Reset Turn to release Control station 1 mushroom head Ø 40 mm push-button, red, trigger composition action 1 NC + 1 NC

Complementary

Black
Black
1 entry for ISO M20 cable gland
80 mm
77 mm
80 mm
0.830 kg
Ex tb IIIC T85°C Db IP65
300000 cycles
10 A cartridge fuse type gG
3 A at 240 V, AC-15, A600 6 A at 120 V, AC-15, A600 0.1 A at 600 V, DC-13, Q600 0.27 A at 250 V, DC-13, Q600 0.55 A at 125 V, DC-13, Q600 1.2 A at 600 V, AC-15, A600

Environment

Ambient air temperature for operation	-2060 °C	
Overvoltage category	I conforming to IEC 60536	
IP degree of protection	IP65 conforming to IEC 60529	
Standards	EN 60079-0:2009	
	EN 60079-31:2009	
	EN 60947-5-4	
	EN 61000-6-2	
	EN/IEC 60947-1	
	EN/IEC 60947-5-1	
	IEC 60079-0:2007	
	IEC 60079-31:2008	
	EN 60947-5-5	
	EN/ISO 13850	
Directives	94/9/EC - ATEX directive	
Dust zone	Zone 21 - 22	
Product certifications	INERIS 04ATEX0023X	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10 cm
Package 1 Width	10 cm
Package 1 Length	23 cm
Package 1 Weight	922 g
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Height	1.3 cm
Package 2 Width	9 cm
Package 2 Length	1.55 cm
Package 2 Weight	845 g

Offer Sustainability

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
☑ China RoHS Declaration
€Yes