




## HUSQVARNA 525BX

Powerful and well-balanced handheld blower for professional use. The patented X-torq engine technology in combination with the special fan and housing design means high blowing capacity that is easy to control. The anti-vibration system Low Vib makes work less strenuous – even during long shifts. And all intuitive controls, i.e. Cruise Control, contribute to efficient and convenient operation at all times.



### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



### Adjustable tube length

The blowing tube length is adjustable for best performance.

### X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



### Cruise control

Fan speed can be set for easier handling.



FEATURES

- X-Torq® engine cuts emission and fuel consumption
  - Adjustable tube length
  - Auto return stop switch for easy starting
- Air speed cruise control
  - Easy to operate with in lined air outlet

Technical specifications	
CAPACITY	
Air flow in housing	14 m³/min
Air flow in pipe	13 m³/min
Air speed (flat nozzle)	86 m/s
Air speed (round nozzle)	70 m/s
DIMENSIONS	
Article gross weight	7660 g
Article net weight	6500 g
Product size height	35 cm
Product size length	28 cm
Tube length	550 mm
Weight	4.3 kg
ENGINE	
Cylinder displacement	25.4 cm³
Electrode gap	0.65 mm
Fuel tank volume	0.45 l
Fuel consumption	518 g/kWh
Idling speed	3000 rpm
Maximum power speed	7300 rpm
Power output	0.9 kW
Spark plug	NGK BPMR8Y
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	91 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) handle	1.2 m/s²
Engine Family CARB	FHQZS.0254GQ
Exhaust emissions (CO average)	379.85 g/kWh
Exhaust emissions (CO average)	988 g/kWh
Exhaust emissions (HC average)	25.99 g/kWh
Exhaust emissions (NOx average)	0.29 g/kWh
Packaging height	400 mm
Packaging length	460 mm
Packaging volume	71.76 dm³
Packaging width	390 mm
Weight incl. packaging	8 kg