

# VCCF4

## TeSys Vario - emergency stop switch disconnecter - 80 A - back of enclosure



### Main

Range	TeSys
Product name	TeSys VARIO
Device short name	VCCF
Product or component type	Emergency stop switch disconnecter
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Network type	AC DC
Control type	Rotary handle
Rotary handle mounting style	Extended
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

### Complementary

Marking	0 - 1
Mounting support	Switch mounting on plate Switch mounting on symmetrical rail Handle mounting on door
Fixing mode	By screws for switch By clips for switch By 4 screws for handle
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	80 A
[Ithe] conventional enclosed thermal current	63 A
[Ie] rated operational current	57 A (AC-23) at 400 V
Rated operational power in W	30 kW 400...415 V (AC-23A) 18.5 kW 230...240 V (AC-23A) 37 kW 500 V (AC-23A) 30 kW 690 V (AC-23A) 30 kW 500 V (AC-3) 22 kW 400...415 V (AC-3) 15 kW 230...240 V (AC-3) 18.5 kW 690 V (AC-3)
Intermittent duty class	30
Making capacity ( I Rms)	800 A 400 V (AC-23A) 800 A 400 V (AC-22A) 800 A 400 V (AC-21A)
[Icm] rated short-circuit making capacity	2.1 kA 400 V at Ipeak
[Icw] rated short-time withstand Rms current	960 A 400 V during 1 s
Rated conditional short-circuit current	10 kA 400 V - associated fuse 80 A gG 10 kA 400 V - associated fuse 80 A aM
Breaking capacity	640 A 400 V AC-23A 640 A 400 V AC-22A 640 A 400 V AC-21A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Device composition	Handle Switch Shaft extension
Mechanical durability	30000 cycles
Electrical durability	30000 cycles DC-1...5 30000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit : screw clamp terminals cable 16 mm <sup>2</sup> - cable stiffness: flexible - with cable end cable end Power circuit : screw clamp terminals cable 25 mm <sup>2</sup> - cable stiffness: solid -
Tightening torque	Power circuit : 4 N.m - on screw clamp terminals
Handle front plate dimension	60 x 60 mm
Height	83 mm
Width	60 mm
Product weight	0.68 kg
Compatibility code	Main switch disconnecter

## Environment

Standards	IEC 60947-3
Product certifications	CCC CSA GL UL
Protective treatment	TC
IP degree of protection	IP65 IP20 conforming to IEC 60529
Mechanical robustness	Shocks 11 ms 30 Gn IEC 60068-2-27 Vibrations 10...150 Hz 1 gn IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0733 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference contains SVHC above the threshold - <a href="#">go to CaP for more details</a>
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations