

RS PRO 850W Fully Modular Power Supply

Stock No: 242-0548

Special Features

- **Modular Cable Configuration** - A Modular cable management design lets you use only the cables you need. You get to save space and create a cleaner-looking build and improve airflow.
- **80 Plus Gold Certification** - 80 Plus Gold certified with 90% efficiency, high efficiency operation lowering energy consumption, noise, temperatures and less energy gets wasted during power conversion, the lower the operating costs will be for the user.
- **105°C-Rated Capacitors** - Using industrial-grade electrolytic capacitors, 2420548 power supplies offer the fixed power and long-term reliability.
- **Silent Operation** - A 120mm Black rifle bearing fan with a zero RPM fan mode option ensuring it is kept down to a minimum at full loads but the fan doesn't spin until you need it, for near-silent operation at low and medium loads.
- **All Black Look** - Black is the colour with black flat cables, black connectors and an all black finish give your gaming PC a clean professional high-tec look.
- **Flat Black Cables** - With flat black cables, PC builders can easily manage space creating a nice clean build with minimal fuss.
- **Warranty** - The CWT 2420548 PSU comes with 12 Months Warranty.













Power Distribution

AC Input	100-240VAC		12A	47-63Hz	
DC Output	+3.3A	+5V	+12V	-12V	+5VSB
Max. Output Current	20A	20A	70.5	0.3A	2.5A
Max. Combined Wattage	110W		846W	3.6W	12.5W
	850W				



Connector Quantity

1 x 20+4	1 x 4+4	1 x 4+4	2 x 6+2 PCIe	2 x 6+2 PCIe	2 x 6+2 PCIe	4 x SATA	4 x SATA	4 x Molex & 1 x FDD
								
495mm	600mm	600mm	PCIe (To 1st Connector) 500mm PCIe (To 2nd Connector) 620mm	PCIe (To 1st Connector) 500mm PCIe (To 2nd Connector) 620mm	PCIe (To 1st Connector) 500mm PCIe (To 2nd Connector) 620mm	Peripheral Cable 2 (To 1st connector) 500mm(SATA) Peripheral Cable 2 (To 3rd connector) 820mm(SATA)	Peripheral Cable 2 (To 2nd connector) 660mm(SATA) Peripheral Cable 2 (To 4th connector) 970mm(SATA)	Peripheral Cable 3 (To 1st connector) 500mm(SATA) Peripheral Cable 3 (To 3rd connector) 820mm(SATA)
						Peripheral Cable 3 (To 2nd connector) 660mm(SATA) Peripheral Cable 3 (To 4th connector) 970mm(SATA)	Peripheral Cable 3 (To 1st connector) 500mm(SATA) Peripheral Cable 3 (To 2nd connector) 660mm(SATA) Peripheral Cable 3 (To 3rd connector) 820mm(SATA) Peripheral Cable 3 (To 4th connector) 970mm(SATA)	Peripheral Cable 1 (To 1st connector) 500mm(4 Pin Molex) Peripheral Cable 1 (To 3rd connector) 770mm(4 Pin Molex)
								Peripheral Cable 1 (To 2nd connector) 630mm(4 Pin Molex) Peripheral Cable 1 (To 4th connector) 920mm(4 Pin Molex) Peripheral Cable 1 (To 5th connector) 1070mm(FDD)

Safety: CB, CE, LVD, RoHS, cTUV US & TUV **CE CB** 
 Protection Features: OVP / SCP / OPP / OTP / OCP
 Dimensions: (W) 150 x (H) 85 x (D) 140mm

RS Stock No: