

Orthomat® Lite



- Cost effective anti fatigue matting
- Offers the user relief from fatigue caused by standing
- Insulates against cold concrete floors
- Ideal for medium use in dry environments
- Pebble surface provides additional traction

Technical Specifications:

- Manufactured from 100% closed cell vinyl foam
- Product height: 6mm

Dimensions (m.)	Weight (Kg)	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.9m x 1.5m	6.4			1		Black	CV010002
0.9m x 2.0m	8.6			1		Black	CV010003
0.9m x 3.0m	12.6			1		Black	CV010004

Material:	Virgin Closed Cell PVC (Foam)
Surface Finish:	Pebble
Product Height:	6mm nominal
Operating Temperature:	0°C to + 60°C
Resistance to Chemicals:	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. Resist alcohol's, aliphatic hydrocarbons, oils , weak acids, strong mineral acids and alkalis. Resists oil and grease if properly cleaned. Does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact the sales office for more specific details.
Environmental Resistance:	Suitable for dry indoor environments.
UV Resistance:	N/A
Typical Applications:	Production lines, assembly areas, packing stations, workbenches.
Installation Method:	Loose lay.
Cleaning Method:	Brush/Mop the top surface.
Product Performance:	Conforms to slip resistance test EN13552 Category R10
Flame Retardancy:	Conforms to FMVSS 302. Fire tested to DIN54332(B2) Part of DIN4102 Will not burn after the ignition source is removed. When 'forced' to burn, Carbon Monoxide, Carbon Dioxide and Hydrogen Chloride fumes are emitted.
Country of Origin:	China

End of document