

EU-MATERIAL SAFETY DATA SHEET

according to guidelines 91/155/EWG

Issue 064/03 from 04.06.98
replaces 064/02
page 1 of 3**TECAST T****ENGLISH****1.1 MATERIAL/PRODUCT IDENTIFICATION**

TRADENAME: TECAST T

1.2 COMPANY IDENTIFICATION

EMERGENCY NUMBER:

2.1 COMPOSITIONCHEMICAL COMPOSITION: Based on polyamide 6 (polymer on ϵ -caprolactam), possibly containing pigments, dyes and additives.**2.2 INFORMATION ON INGREDIENTS**The proportion of monomer (ϵ -caprolactam) is max. 2 - 3 %. ϵ -caprolactam:**3. POTENTIAL RISKS**

This product is not harmful.

4. FIRST AID MEASURES

INHALATION: After accidental inhalation of fumes or thermal decomposition products, using self-protection, remove the person from the danger zone and apply artificial respiration if necessary. Seek medical help and keep quiet and warm.

SKIN CONTACT: After contact with molten polymer, immediately cool with cold water for a prolonged time. Remove affected clothing. Do not peel polymer from skin. Cover burns with sterile dressings. Obtain medical attention.

EYE CONTACT: If a foreign body (splinter, chip) enters the eye do not rub. Rinse immediately with plenty of water. Seek medical attention.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water, foam, dry powder, carbon dioxide

UNSUITABLE EXTINGUISHING MEDIA: None known

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTING: Wear self contained breathing apparatus.

ADDITIONAL ADVICE: This product ignites in a flame and continues to burn on removal of the source. With thermal decomposition toxic and combustible gasses and steam are released. There is a danger of the fire spreading through spontaneous ignition of the gaseous decomposition products. Molten product must therefore be cooled with water.
Water used to extinguish the fire and fire remainders must be collected. Fire hydrants must be controlled and water disposed of, in accordance with local regulations.

EU-MATERIAL SAFETY DATA SHEET

according to guidelines 91/155/EWG

issue 064/03 from 04.06.98
replaces 064/02
page 2 of 3

TECAST T

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS: Before entry of swarf waste to sewage it should be mechanically cleaned of product remainders.

METHODS FOR CLEANING UP: Mechanical

7.1 HANDLING

GENERAL ADVICE: Avoid overheating of material by improper handling.
Avoid dust generation.

TECHNICAL MEASURES: For mechanical operations local extraction / ventilation is recommended to ensure that less than the 8.1 limit is achieved. Where dust is produced, measures must be taken to avoid static electricity discharge.

7.2 STORAGE

GENERAL ADVICE: The appropriate company regulations for fire prevention are to be followed.

SPECIAL REQUIREMENTS: None.

8.1 EXPOSURE CONTROLS

GUIDELINES FOR MATERIALS WITHIN THE WORKINGPLACE:

For mechanical operations the following are to be observed (TRGS 900, Standard 1997):

Respirable dust: MAC 6 mg/m³

ϵ -caprolactam (dust and vapours): MAC 5 mg/m³ (measured as total dust),
(CAS 105-60-2) comment „Y“, no risk of embryo damage if MAC is observed.

8.2 PERSONAL PROTECTION

RESPIRATORY PROTECTION: During dusty operations use respiratory protection (e.g. respiratory mask with a combination filter).

EYE PROTECTION: For mechanical operations wear safety glasses with side pieces.

SKIN PROTECTION: Skin protection should be used (barrier cream).

HYGIENE MEASURES: General industrial hygiene regulations are to be observed.
Wash hands before breaks and at the end of workday.
Do not eat, drink or smoke in the workplace.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Solid (semifinished or finished parts)

COLOUR: Various, dependent on colourant

ODOUR: Odourless

DENSITY (20 °C): 1,12 - 1,15 g/cm³ DIN 53479

MELTING POINT/RANGE: 210 - 220 °C DIN 53736

DECOMPOSITION TEMPERATURE: > 300 °C DIN 53765-D-10

IGNITION TEMPERATURE: > 400 °C ASTM-D 1929

EXPLOSION LIMITS: Not applicable

SOLUBILITY (20 °C): Insoluble in water
In organic solution applications insoluble



EU-MATERIAL SAFETY DATA SHEET

according to guidelines 91/155/EWG

issue 064/03 from 04.06.98

replaces 064/02

page 3 of 3

TECAST T

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Temperatures > 300 °C (Start of the thermal decomposition)

SUBSTANCES TO AVOID: Concentrated or strong acids, oxidizing media

HAZARDS DECOMPOSITION PRODUCTS:

With carbonization and incomplete combustion toxic gasses develop, predominantly carbon dioxide and carbon monoxide. In addition nitric oxide, amine, ammonia, ε-caprolactam, nitrile, aliphatic and aromatic hydrocarbons, aldehyde, hydrogen cyanide, sulphur dioxide can be generated, as well as small quantities of ketone and acids.

ADDITIONAL INFORMATION: None

11. TOXICOLOGICAL INFORMATION

With proper use and in accordance with regulations there are no known dangers to health. Contact with molten product can cause burns.

12. ECOLOGICAL INFORMATION

Because of insolubility in water separation by filtration or sedimentation is possible.

13. DISPOSAL CONSIDERATIONS

Uncontaminated product can be recycled.

If no use is possible, product waste can, in accordance with official local regulations, be mixed with household waste or incinerated in an appropriate place.

Waste product code No. for uncontaminated product (valid for Germany): 57111 polyamide waste

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

15.1 EU GUIDELINES

No warning necessary.

15.2 NATIONAL REGULATIONS (GERMANY)

GefStoffV (26.10.93): No warning necessary

WHG (12.11.96): Not classified

16. OTHER INFORMATION

This data sheet is valid for

TECAST T
TECAST M
TECAST TM
TECAST R
TECAST L
TECAST ST

This statement is valid for pure product. It is based on our current knowledge and offers no assurance of properties. It is the user's responsibility to ensure that existing legislation and regulations are followed.

