



Datasheet

RS PRO 0.5m DisplayPort Male to Male Cable - Black

Stock number: 186-3022

EN



Our RS PRO 0.5 metre DisplayPort cable comes with 2 latching, 20 pin male connectors, although only 19 pins are connected. Pin 20 carries 3.3v which traditionally is not used and can cause problems with some devices, this is why only 19 pins are connected on our product.

The connector hoods are made from black PVC and come with dust caps to protect the connectors. On top of the connector is the latch release and a strain relief on the end of the hood to support the cable.

Our 0.5m DisplayPort cable is v1.2 and has a bandwidth of 21.6 Gbit/s.

DisplayPort, commonly known as DP is a digital high definition video connection which also can carries audio. Due to its bandwidth, DisplayPort cables are normally up to 5 metres long.

DisplayPort cables are very simple to use and are plug and play. Care must be taken when unplugging them to make sure that the latches have been released before pulling out the connector.



9	LDPE	4	g
8	45P Black PVC	10	g
7	H.S.T:±1.5 20mm*2pcs.	0.04	m
6	DisplayPort Port M 28AWG Clam	2	pcs
5	DisplayPort M Dust cap	2	pcs
4	DisplayPort M(DP01#)ABS Top shell color:Black	2	pcs
3	DisplayPort (DP01#) M ABS bottom shell color:Black	2	pcs
2	DisplayPort Port M Solder insulation:Black shell gold plated pin gold plated	2	pcs
1	DP~[28AWG(7/0.127TC+EAM)*5P+28AWG(7/0.127TC)*4C+AEB(50%ALMG)OD:7.3MM~Jacket color:Black ~Mark:DisplayPort Cable E342987 兄 AWM STYLE 20276 80℃ 30V VW-1	0.52	M

RoHS / REACH / CE

rspro.com