

DuraJack™

durajack.com

DPE-554TQ Hydraulic Electric/Torque Wrench Pump

- ※ External adjustable pressure regulator.
- ※ Retract side internal relief valve protects tool.
- ※ SPE-554TQ series: just use with Hydraulic Torque Wrench.
- ※ SPE-554TQJ series: just use with Hydraulic lift applications.
- ※ Opt eight 1/4" ports (include female and male couplers with dust cap), that can synchronize work for 4 hydraulic wrench.
- ※ It can be set automatic stop moving as motor idle running till 20、40、60 seconds and pressure release.
- ※ Safety start: After stopping, need to press another start button to continue.
- ※ Heat Exchanger Kit: Design air cooling to avoid pump overheating and costly repair from long work periods.




DPE-554TQ Series

Reservoir Capacity:
8-20 L

Flow at rated pressure:
0.9-11.3 L

Motor Size:
0.84 kW(1-1/8hp)

Maximum Operating Pressure:
700 bar



Custom build your Electric Pump:

DPE-554TQ 2 6 1 8 2 CWG

0 1 2 3 4 5 6

0.Type

TQ= just use in Torque Wrench
TQJ= using in lift applications

1.Voltage
1=115V
2=230V

2.Hz
5=50Hz / 60Hz

3.Phase
1=single phase

4. Reservoir (Lx0.26=gal)
8=8L (2.1gal)
20=20L (5.2gal)
★ User can order suitable reservoir.

5.Manifold (include 1/4" male-female coupler)
1=1 manifold with 1 male and 1 female coupler
2=1 manifold with 2 male and 2 female couplers (standard)
3=1 manifold with 3 male and 3 female couplers
4=1 manifold with 4 male and 4 female couplers

6.Optional
W=Wheel
O=Cool system
G=Pressure Gauge

Model Number	Rpm	dBA at Idle and 700bar	Motor kW (hp)	Amp at 700bar	Flow rate @115VAC(L/min)				Oil tank (L)	Usable oil (L)	Weight (with oil) (kg)
					0 (bar)	50 (bar)	350 (bar)	700 (bar)			
DPE-554TQ	12000	80	0.84 (1-1/8)	25 /110V	11.3	7.1	1.2	0.9	8	7	32
				13 /230V							