

# Data sheet CABLE

RS Stock No. 433-4212



TYPE S THERMOCOUPLE CABLE									
<b>SECTION :</b>									
<ul style="list-style-type: none"> <li>0.22 mm<sup>2</sup></li> </ul>									
<b>DIAMETER :</b>									
<ul style="list-style-type: none"> <li>∅4 mm</li> </ul>									
<b>INSULATION :</b>									
<ul style="list-style-type: none"> <li>PTFE/Copper braid/PTFE</li> </ul>									
<b>MAXIMAL TEMPERATURE :</b>									
<ul style="list-style-type: none"> <li>-20/105°C</li> </ul>									
<b>PAKAGING :</b>									
<ul style="list-style-type: none"> <li>25 m</li> </ul>									
<b><u>Other Dimensions :</u></b>									
<table border="1"> <thead> <tr> <th>Type</th> <th>S</th> </tr> </thead> <tbody> <tr> <td>Insulation</td> <td></td> </tr> <tr> <td>PTFE/TC/PTFE 200°C</td> <td>433-4183</td> </tr> <tr> <td><b>PVC/TC/PVC -20/105°C</b></td> <td><b>433-4212</b></td> </tr> </tbody> </table>		Type	S	Insulation		PTFE/TC/PTFE 200°C	433-4183	<b>PVC/TC/PVC -20/105°C</b>	<b>433-4212</b>
Type	S								
Insulation									
PTFE/TC/PTFE 200°C	433-4183								
<b>PVC/TC/PVC -20/105°C</b>	<b>433-4212</b>								