



# trip unit TM125DC, ComPact NSX 160 DC, thermal magnetic, 125 A rating, 3P 3d

LV438136

Discontinued on: 30 September 2022

Important message: This product has been switched to new ComPacT range and is no longer commercialized. It will continue to be available until Q4 2022 only limited to specific projects.

#### Main

Range	ComPact
Range of product	ComPact NSX100250 DC
Product or component type	Trip unit
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Range compatibility	ComPact NSX160 DC
Device application	Distribution
Number of poles	3P
Protected poles description	3t
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rated current	125 A at 40 °C
[Ue] rated operational voltage	750 V DC
Network type	DC

#### Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.71 x ln
Long-time protection delay adjustment type tr	Fixed
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick- up adjustment range	1250 A
Short-time protection delay adjustment type tsd	Fixed
Earth-leakage protection	Without

### **Environment**

Standards	IEC 60947-2
Product certifications	KEMA ASEFA LCIE ASTA
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

## **Packing Units**

Package 1 Weight 387.0 g  Package 1 Height 6.8 cm  Package 1 width 9.8 cm  Package 1 Length 11.2 cm  Unit Type of Package 2 S03  Number of Units in Package 2 28  Package 2 Weight 11.323 kg  Package 2 Height 30.0 cm	Unit Type of Package 1	PCE
Package 1 Height 6.8 cm  Package 1 width 9.8 cm  Package 1 Length 11.2 cm  Unit Type of Package 2 S03  Number of Units in Package 2 28  Package 2 Weight 11.323 kg  Package 2 Height 30.0 cm	Number of Units in Package 1	1
Package 1 width  Package 1 Length  11.2 cm  Unit Type of Package 2  Number of Units in Package 2  Package 2 Weight  11.323 kg  Package 2 Height  30.0 cm	Package 1 Weight	387.0 g
Package 1 Length 11.2 cm  Unit Type of Package 2 S03  Number of Units in Package 2 28  Package 2 Weight 11.323 kg  Package 2 Height 30.0 cm	Package 1 Height	6.8 cm
Unit Type of Package 2 S03  Number of Units in Package 2 28  Package 2 Weight 11.323 kg  Package 2 Height 30.0 cm	Package 1 width	9.8 cm
Number of Units in Package 2 28  Package 2 Weight 11.323 kg  Package 2 Height 30.0 cm	Package 1 Length	11.2 cm
Package 2 Weight 11.323 kg Package 2 Height 30.0 cm	Unit Type of Package 2	S03
Package 2 Height 30.0 cm	Number of Units in Package 2	28
	Package 2 Weight	11.323 kg
Package 2 width 30.0 cm	Package 2 Height	30.0 cm
	Package 2 width	30.0 cm
Package 2 Length 40.0 cm	Package 2 Length	40.0 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## **Contractual warranty**

Warranty 18 months
--------------------

### Recommended replacement(s)

LV438136 is replaced by:



Trip unit TM125DC, ComPacT NSX160 DC, 3 poles, thermal magnetic protections, 125A rating

C163TM125D