



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VC-GUN |
| Product or component type | Enclosed emergency stop switch disconnecter |
| Performance level | High performance |
| Poles description | 3P |
| Control type | Rotary handle |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Rotary handle padlocking | 1 to 3 padlocks 4...8 mm |

Complementary

| | |
|--|---|
| Marking | 0 - 1 |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ithe] conventional enclosed thermal current | 32 A |
| [Ie] rated operational current | 29 A (AC-23A) at 400 V |
| Rated operational power in W | 15 kW at 400 V (AC-23) 11 kW at 400 V (AC-3) |
| Intermittent duty class | 30 |
| Making capacity (I rms) | 400 A at 400 V AC-21A 400 A at 400 V AC-22A 400 A at 400 V AC-23A |
| [Icm] rated short-circuit making capacity | 1 kA at 400 V at Ipeak |
| [Ith] conventional free air thermal current | 32.0 A conforming to IEC 690 V 25 A conforming to UL 600 V |
| Rated power in hp | 5 Hp at 240 V, UL certified 10 Hp at 480 V, UL certified 15 hp at 600 V, UL certified |
| [Icw] rated short-time withstand Rms current | 480 A at 400 V duration: 1 s |
| Rated conditional short-circuit current | 10 KA at 400 V - associated fuse 50 A aM 10 kA at 400 V - associated fuse 50 A gG |
| Breaking capacity | 320 A at 400 V (AC-21A) 320 A at 400 V (AC-22A) 320 A at 400 V (AC-23A) |
| Mechanical durability | 100000 cycles |
| Electrical durability | 100000 Cycles AC-21 30000 cycles DC-1...5 |
| Environmental characteristic | Standard environment |
| Suitability for isolation | Yes |
| Connections - terminals | Screw clamp terminals 10 mm ² - solid - with cable end Screw clamp terminals 6 mm ² - flexible |
| Tightening torque | 2.1 N.m - on screw clamp terminals |
| Fire resistance | 960 °C conforming to IEC 60595-2-1 |
| Handle front plate dimension | 60 x 60 mm |
| Height | 164 mm |
| Width | 121 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------|--------|
| Depth | 132 mm |
| Net weight | 0.5 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60204 CSA C22.2 No 14 UL 508 IEC 60947-4-1 |
| Protective treatment | TC |
| IP degree of protection | IP65 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 12 |
| Mechanical robustness | Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27 |
| Ambient air temperature for operation | -20...50 °C |

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 662 g |
| Package 2 Weight | 11.056 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|