


FEATURES

- Single row tapered roller bearing
- Accommodates combined radial and axial loads
- Low frictional moments during operation
- Seperable rings
- Pressed steel cage

Tapered Roller Bearing 35x80x32.75mm

RS Stock No.: 2482855



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.




Product Description

A range of RS Pro single row Tapered Roller Bearings, offering versatility and overall high performance. RS Pro Tapered Roller bearings utilise a high strength steel cage and optimised internal geometry to ensure adequate operation.

General Specifications

Bearing Type	Single Row Tapered Roller Bearing
Number of Rows	1
Material	Steel
Race Type	Tapered
Bore Type	Cylindrical
Application	Pumps, Gearboxes, Motors
Material of cage	Pressed steel





Mechanical Specifications

Inside Diameter (d)	35mm
Outside Diameter (D)	80mm
Cone Width (B)	31mm
Cup Width (C)	25mm
Assembled Width (T)	32.75mm
Dynamic Load Rating	103kN
Static Load Rating	116kN
Limiting Speed	9000rpm
Mass	0.83kg

Operation Environment Specifications	
Temperature Range	-15°C to 120°C
Temperature Kange	-13 C to 120 C



INCLUDES WITH PRODUCT / STANDARD ACCESSORIES / CONSTRUCTIONAL DIAGRAM