

Hand Pallet Truck AC Series

- R**ubber coated handle comfortable even under extreme temperature conditions.
- F**ully sealed galvanized hydraulic unit housing.
- S**ingle valve cartridge for easy maintenance.
- P**owder coated chassis made of high grade steel.
- L**ead-in and lead-out rollers reduce damage to pallets.



One valve cartridge



Two nylon entry and exit rollers



polyurethane

nylon

rubber

polyurethane

nylon

polyurethane

Technical Specifications

Model	AC20S	AC20L	AC25S	AC25L	AC30S	AC30L
Capacity (kg)	2000	2000	2500	2500	3000	3000
Lifting Height (mm)	115					
Min. Fork Height (mm)	85 (75)					
Max. Fork Height (mm)	200 (190)					
Fork Length (mm)	1150	1220	1150	1220	1150	1220
Overall Width (mm)	540	685	540	685	540	685
Fork Width (mm)	160					
Load Roller (mm)	Tandem Φ 82x70, Single Φ 82x93 Nylon, Polyurethane					
Steering Wheel (mm)	Φ 200x50 Nylon, Polyurethane or Rubber					
Net Weight (kg)	80	83	82	85	85	87

Special fork length available: 800, 950, 1000, 1500, 2000mm.