



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	24 V
Product or component type	Replacement battery cartridge
Main Output Voltage	24 V
Battery type	Lead-acid battery
Provided equipment	User manual

Batteries & Runtime

Battery location	Internal battery
Number of battery blocks per string	6
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Built-in
Battery voltage	24 V
Number of battery replacement quantity	2

Physical

Colour	Black
Height	151 mm
Width	99 mm
Depth	132 mm
Net weight	5.32 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Output

Battery capacity	9 Ah
------------------	------

Conformance

Product certifications	UL 1778 5th edition
Standards	UL 1778 5th edition

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...85 %
Ambient air temperature for storage	-15...50 °C
Storage altitude	0.00...3048.00 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.5 cm
Package 1 Width	39.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	23 kg
SCC14	50731304428096

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------