

Datasheet

RS PRO KRB 0560 tool for crimping non-insulated open-barrel terminals, 6.3/250 B/F crimp, 0.5 - 6 mm²


Stock No: 297-2963




Features & Benefits:

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miss-crimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

Crimp Die Set



Crimp Profile



TECHNICAL DATA

Length: 256 mm/10.08"

Width: 22 mm/0.87"

Height: 80 mm/3.15"

Weight: 560 gr/1.23 lb

Wire size: 0.5-6 mm² / AWG 22-AWG 10

Crimp dimensions mm/mm²:

0.5 – 1.5 mm²/1.5 – 2.5 mm²/4 - 6 mm²

Crimp dimensions inch/AWG:

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 - AWG 10

Connector: Uninsulated open barrel connectors

Description: For uninsulated 250 series open barrel tabs and receptacles.

Life span, cycles: 50,000