

FEATURES

- Robust machined
 alloy construction
- Small and lightweight with high output
- Brushless drive motor
- Smooth pulseless liquid flow
- Reliable impeller operation
- Output signal for performance monitoring

RS PRO, 12 V 345 mbar Direct Coupling Water Pump, 2L/min

RS Stock No.: 702-6876



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

High quality miniature pump range for liquids. Ideal for many general applications, including research and development, medical or aeronautical industries, miniature and portable equipment. These pumps use a centrifugal principle to deliver smooth pulseless flow. They are exceptionally quiet and reliable with a brushless drive motor. A signal output wire can be used, optionally, to provide information of status and pump speed/output.

General Specifications

Туре	Direct Coupling Water Pump
Maximum Flow Rate	3L/min
Input Connection	3.2mm Tube
Input Connection Size	3.2mm
Output Connection Size	3.2mm
Maximum Head	3.5m
Maximum Pressure	345bar
Body Material	Anodised Aluminium;
Coupling Type	Direct
Maximum Fluid Temperature	100°C
Application	General applications (research, development), Medical, Aeronautical Industry, Portable equipment, Oil Refineries, Power plants, Municipal water applications
Usage Instructions	This pump in not self-priming and has to be filled before starting.

Electrical Rating

Supply Voltage	12V
Input Power	6W

Protection Category	
IP Rating	IP52







