




0	Creation	BLONDEL N.	03.05.2006	DP	03.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :
TYPE J NOZZLE M6 x 100 E06007		N° 621-2259			
		Material :		Scale :	
		-		N.T.S	
		<small>unless otherwise specified Generale tolerances \pm 0.1 mm</small>			
<small>94-05-08-TE-079 R6v.2</small>					



6	Heat shrink	PE
5	Sleeve	PE
4	Cable	FG/S.SBraid
3	Spring	AISI 302
2	Bolt	AISI 303L
1	Nozzle	AISI 304L

Tag	Description	Material
-----	-------------	----------

0	Creation	BLONDEL N.	03.05.2006	DP	03.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :

TYPE J NOZZLE M6 x 100 E06007	N° 621-2259
----------------------------------	--------------------

	Material : -	Scale : N.T.S
	<small>unless otherwise specified Generale tolerances ± 0.1 mm</small>	 <small>94-05-08-TE-079 Rév.2</small>

Description

Type J Nozzle

Thermocouple type

J

Grounded or Ungrounded

Grounded

According to IEC-BS 4937 60584-2 & IEC-BS 4937 60584-3

RoHS compliance

Yes

Accuracy Class 2

±2.5°C or ±0.0075xT

Colour Codes IEC 60584

+VE arm	black
-VE arm	white
overall	black

Temperature

Range	-50 to +750° C
Operating	-50 to +400° C

Cable characteristics

Section	7x0.2
Conductor	0.22 mm²
Insulation	Glass fiber
Braid	StainlessSteel
Length	2000 mm

Nozzle dimensions

M6 x 100

Connection

Swivel mounted

Application

Plastic
Mould Industry

0	Creation	BLONDEL N.	03.05.06	DP	03.05.06
Ind.	Object	Drawn :	Date :	Checked :	Date :

**TYPE J NOZZLE M6 x 100
E06007**

N° 621-2259



Material :

Scale :

N.T.S

Unless otherwise specified generales tolerances ± 0,1mm

