



Specifications:

Material : Fiberglass
 Colour : Silver-Gray
 Heat treated for minimal fraying. Withstands temperature to 1200° F
 Easily Expanded for ease of installation

**RoHS
 Compliant**

Properties:

Flexibility : Excellent
 Solvent Resistance : N/A
 Abrasion Resistance : N/A
 Low Temperature Brittleness : NEMA VS-1, -75°C
 Thermal Aging (Continuous Operation) : NEMA VS-1, 250°C
 Flammability : NEMA VS-1, non-combustible

Part Number Table

Description	Size	Inside Diameter in (mm)		Wall Thickness in (mm)	Part Number
		Max.	Min.	Min.	
Heat Treated Fiber glass Sleeving	24AWG	0.027 (0.96)	0.02 (0.51)	0.005 (0.13)	SPC4913
	22AWG	0.032 (0.81)	0.025 (0.64)	0.005 (0.13)	SPC4914
	20AWG	0.039 (0.99)	0.032 (0.81)	0.009 (0.23)	SPC4915
	18AWG	0.049 (1.25)	0.04 (1.02)	0.011 (0.28)	SPC4916
	16AWG	0.061 (1.55)	0.051 (1.3)	0.011 (0.28)	SPC4917
	14AWG	0.074 (1.88)	0.064 (1.63)	0.011 (0.28)	SPC4918
	12AWG	0.091 (2.31)	0.081 (2.06)	0.011 (0.28)	SPC4919
	10AWG	0.112 (2.8)	0.102 (2.6)	0.011 (0.28)	SPC4920
	8AWG	0.141 (3.6)	0.129 (3.3)	0.011 (0.28)	SPC4921
	6AWG	0.178 (4.5)	0.162 (4.1)	0.013 (0.33)	SPC4922
	4AWG	0.224 (5.7)	0.204 (5.2)	0.016 (0.41)	SPC4923
	2AWG	0.278 (7.1)	0.258 (6.6)	0.016 (0.41)	SPC4924
	0AWG	0.347 (8.8)	0.325 (8.3)	0.016 (0.41)	SPC4925
	3/8"	0.399 (10.1)	0.375 (9.5)	0.016 (0.41)	SPC4926
	7/16"	0.462 (11.7)	0.438 (11.1)	0.018 (0.46)	SPC4927
	1/2"	0.524 (13.3)	0.5 (12.7)	0.018 (0.46)	SPC4928
	5/8"	0.655 (16.7)	0.625 (15.9)	0.018 (0.46)	SPC4929
3/4"	0.786 (20)	0.75 (19.1)	0.018 (0.46)	SPC4930	
1"	1.036 (26.3)	1 (25.4)	0.018 (0.46)	SPC4932	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.