

Product data sheet

Characteristics

A9E15122

2 ways low level switch iCME 10 A 0,1..5 CA
0,05..3 CCA 2P U 1..440 VAC/VCCV CA



Main

Range of product	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICME
Device application	Electrical circuit control
Contacts type and composition	1 NO + 1 NC
Standards	EN 60947-3 IEC 60947-3 VDE 0660 part 107 UL

Complementary

Maximum operating voltage	440 V
Control type	Rotary handle 2 positions
Marking	1 - 2
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Net weight	44 g
Colour	White
Mechanical durability	1000000 cycles
Electrical durability	AC-21A: 200000 cycles
Connections - terminals	Jumper terminals 1.5 mm ²
Wire stripping length	9 mm for downside connection
Tightening torque	1 N.m downside

Environment


IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

Packing Units

Package 1 Weight	67 g
Package 2 Weight	5.847 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------