



ENGLISH

Datasheet

## RS Pro DIN Rail Enclosure, Polycarbonate, 75 x 22.5 x 98.5mm

RS Stock No: **243-3632**



### Product Details

RS Pro DIN rail enclosure measures 75 x 22.5 x 98.5 mm and has polycarbonate construction for added durability. The easily removable front cover easily adapts for external components such as indicators or switches. The performed pins allow simple connection from PCB to terminals.

### Features and Benefits

- Constructed from fully insulated polycarbonate to UL 94V-2
- Preformed pins allow simple connection from PCB to terminals
- Equipment can be fully assembled prior to location in housing
- Captive self locking terminal screws give high resistance to vibration
- Front cover easily removed and can be drilled or adapted for external components such as indicators or switches
- Integral guide rails for PCB location in multiple positions
- Removable front cover



ENGLISH

### Specifications:

Body Material	PC
Colour	Grey
DIN Rail Type	Top Hat
Enclosure Rating	IP20
Internal Mounting Type	PCB Mounted
Special Features	Plug In, Removable Front Cover
Standards Met	UL E84703; CSA LR 62504; RoHS Compliant
Terminal Type	Solder
Dimensions	75 x 22.5 x 98.5 mm
Height	98.5 mm
Length	75 mm
Maximum Operating Temperature	+110°C
Maximum Terminals	12
Minimum Operating Temperature	-40°C
Width	22.5 mm
Enclosure Type	DIN Rail