



### Main

|                                    |  |
|------------------------------------|--|
| Product or component type          | Short rear connection  |
| Accessory / separate part category | Connection accessory   |
| Range compatibility                | ComPacT new generation (ComPacT NSX100 new generation)<br>ComPacT new generation (ComPacT NSX160 new generation)<br>ComPacT new generation (ComPacT NSX250 new generation)<br>ComPacT new generation Compact NSX100 DC<br>ComPacT new generation Compact NSX160 DC<br>ComPacT new generation Compact NSX250 DC<br>ComPacT new generation (EasyPact CVS100)<br>ComPacT new generation (EasyPact CVS160)<br>ComPacT new generation (EasyPact CVS250)<br>ComPacT new generation (ComPacT INS)<br>ComPacT new generation (Compact INV) |
| Poles description                  | 3P<br>4P   |
| [In] rated current                 | 250 A  |

### Complementary

|                        |          |
|------------------------|----------|
| Location of connection | Rear     |
| Shape                  | Short    |
| Quantity per set       | Set of 2 |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 2.600 cm  |
| Package 1 Width              | 11.200 cm |
| Package 1 Length             | 11.500 cm |
| Package 1 Weight             | 170.000 g |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 10.800 cm |
| Package 2 Width              | 20.100 cm |
| Package 2 Length             | 35.100 cm |
| Package 2 Weight             | 2.227 kg  |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 60        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 40.000 cm |
| Package 3 Length             | 60.000 cm |
| Package 3 Weight             | 11.750 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|