83120

PratiKa industrial socket - 32 A - 3P + E - 380...415 V AC - IP44





Main	
Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Complementary	
Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
[Ue] rated operational voltage	380415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel
Connections - terminals	Captive screws, completely loosened
Cable cross section	2.510 mm²
Cable outer diameter	11.521 mm
Net weight	0.485 kg
Base dimension	106 x 130 mm
Height	130 mm
Width	106 mm
Depth	189 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

Environment

EN 60309-2	
EN 60309-1	
IP44 conforming to IEC 60529	
IK08 conforming to EN 62262	
850 °C conforming to IEC 60695-2-11	
50 % at 40 °C	
70 % at 30 °C	
90 % at 20 °C	
35 °C (86400 s)	
	EN 60309-1 IP44 conforming to IEC 60529 IK08 conforming to EN 62262 850 °C conforming to IEC 60695-2-11 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.7 cm
Package 1 Width	14.8 cm
Package 1 Length	18.9 cm
Package 1 Weight	422.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Height	12.0 cm
Package 2 Width	21.5 cm
Package 2 Length	27.0 cm
Package 2 Weight	935.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	6
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	3.292 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

NA/1	40
vvarrantv	18 months
• •	