



Datasheet

RS PRO Uncoated Ladder Single-Lock Stainless Steel Cable Ties

EN



Technical Information:

Material: Stainless Steel Grade 316

316 grade stainless steel, for extra corrosive environments

Working Temp.: -80°C to +500°C

Description: Entirely Metallic

Flammability: Fireproof

Other Properties: UV-resistant

Product Feature: Strong self-locking mechanism(Pawl and ratchet) saves time on installation;

Flat and low profile head(no sharp edge), for easy installation;

Larger slot at the end, allows the use of a hook-type tool;

Uncoated version for high temperature applications.

Applications: Ideal for petrochemical, industries, power stations, mining, ship-building, offshore, and other aggressive environments.

Specification

RS CODE	EASE CODE	LENGTH		WIDTH		THICKNESS		MAX. BUNDLE DIAMETER		MIN. TENSILE STRENGTH	
		mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
	CT-SS-LS-225/7UC	225	8.9	7.0	0.28	0.28	0.011	62	2.44	1120	250
	CT-SS-LS-300/7UC	300	11.8					81	3.19		
	CT-SS-LS-610/7UC	610	24.0					176	6.93		
	CT-SS-LS-610/12UC	610	24.0	12.0	0.47	0.35	0.014	176	6.93	2500-2800	568-636



