

## **FEATURES**

- These ball spring plungers
- The threaded body has a screwdriver slot
- Available either in black oxide finish or stainless steel
- Retained hardened steel ball
- Temperature range up to 250°C
- Black oxide supplied
  10 per bag
- Stainless steel supplied - 5 per bag

# RS PRO M4 Spring Plunger, 9.8mm Long

**RS Stock No.: 478-567** 



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### Product Description ATTRIBUTE

These Ball Spring Plungers from our own RS PRO brand are ideal for applications where a predefined positional stop is required or positioning a workpiece against a datum face. A ball end spring plungers are available in steel and stainless steel material.

#### **General Specifications**

Туре	Spring Plunger
Body Material	Stainless Steel
Thread Size	M4
Applications	Clamping of adjustable elements, Positioning of work pieces, Latching of mechanisms

### Mechanical Specifications

Length	9.8mm
Ball Diameter	2.5mm

#### **Operation Environment Specifications**


Operating Temperature	Upto 250°C

Approvals	
Compliance/Certifications	RoHS

## Ball & Spring Plungers







Part No.	Α	В	Thread size	Body material
478652	1.5	8	M3	Burnished steel
478636	2.5	10	M4	Burnished steel
478668	3	13	M5	Burnished steel
478658	3.5	15	M6	Burnished steel
478731	5	18	M8	Burnished steel
478737	6	21	M10	Burnished steel
478747	8	25	M12	Burnished steel
478753	10	28	M16	Burnished steel
478664	12	35	M20	Burnished steel
478743	1.5	8	M3	Stainless steel
478567	2.5	10	M4	Stainless steel
478917	3	13	M5	Stainless steel
478927	3.5	15	M6	Stainless steel
478911	5	18	M8	Stainless steel
478573	6	21	M10	Stainless steel
478608	8	25	M12	Stainless steel
478563	10	28	M16	Stainless steel
478923	12	35	M20	Stainless steel

