



### Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	3P
[I <sub>th</sub> ] conventional free air thermal current	16 A
I <sup>2</sup> t on activation	100000 A <sup>2</sup> .s
Number of points	2
Number of cables	3 cable(s) 2.5 mm <sup>2</sup>
Cable length	0.2 m
Quantity per set	Set of 6

### Complementary

[U <sub>i</sub> ] rated insulation voltage	600 V conforming to CSA 600 V conforming to UL 690 V conforming to IEC 60439-1
Peak current	25 kA
Width	36 mm
Height	46 mm
Depth	38 mm
Net weight	0.04 kg






### Environment

Standards	IEC 60439
Product certifications	DNV LRQS (Lloyds register of shipping) UL CSA

### Packing Units

Package 1 Weight	54 g
Package 2 Weight	325 g
Package 3 Weight	5.997 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

---

Warranty

18 months

---