

## **FEATURES**

- Insulation Resistance >= 100 MΩ
- Neoprene O-Ring
- Brass nickel plated coupling nut

# RS PRO M12 FEMALE STRAIGHT TO MALE RIGHT ANGLED 8 PIN 8 WIRE 10m 0.25 sq. mm PVC CABLE

RS Stock No.: 2500702



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



# Product Description ATTRIBUTE 1

# **M12 Connector Cable Assembly**

Brought to you under the trusted RS Brand, this range of M12 connector cable assemblies are commonly used in sensor and automation equipment. Fitted with a secure coupling nut, these RS M12 cable assemblies are an ideal solution for when reliable data transference is needed.

The M12 connector boasts a high degree of environmental protection, and is ideal for industrial use, with applications ranging from process control to commercial electronics.

#### **Features and Benefits:**

- Insulation Resistance >= 100  $M\Omega$
- Neoprene O-Ring
- · Brass nickel plated coupling nut

#### **General Specifications**

Rated Operational Voltage	30 V
Current Rating	2A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C +75°C
Tightening Torque	0.6 Nm
Coding	A-Coded

#### **Material Specifications**

Grip Material	PU
Contact	Cu-Zn
Contact Plating	Gold Flash
Contact Carrier	Nylon 66
O-Ring	Neoprene
Grip Color	Black
Coupling Nut	Brass Nickel-Plated

#### **Cable Specifications**

Cable Length-L	10 m
Cable Type	8 Core PVC Multi Strand

# RS PRO M12 FEMALE TO MALE CONNECTOR



Sheath Color	Black
Cross Section of Wire	0.25 sq. mm
Core Dia	1.3 mm
Cable Dia	6.0 ± 0.1 mm

## **Protection Category**

Dograp of Protection	ID67	
Degree of Protection	IFU/	


## **Additional Information**

Custom Tariff Number	85369090	

### **Approvals**

Standards Met	IEC 61076-2-101

# Connection Diagrams / Assembly Diagrams / Illustrations / Accessories



All Dimensions are in mm.