



HUSQVARNA 350BT

The Husqvarna 350BT is a commercial styled blower in the popular 50 cc mid-size range featuring a new, powerful X-Torq® engine. The harness and controls are ergonomically designed for high capacity and ease of use.



Utilize full blow force with minimal arm strain

The offset handle makes the blow forces easier to control by preventing the arm from being pulled downwards



Easier cold starting

Starting a cold engine requires less effort thanks to the air purge.

X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



Adjustable handles

Adjustable handles for superior comfort.




FEATURES

- X-Torq® engine cuts emission and fuel consumption
- Air purge for easier cold starting
- Offset handle makes the blow forces easier to control
- Adjustable handle increased comfort
- LowVib® reduce vibrations
- Comfortable padded harness

Technical specifications	
CAPACITY	
Air flow in housing	19.6 m³/min
Air flow in pipe	14 m³/min
Air speed	80.47 m/s
DIMENSIONS	
Weight	22.5 lbs
Weight	10.21 kg
ENGINE	
Cylinder displacement	50.2 cm³
Electrode gap	0.7 mm
Fuel tank volume	1.25 l
Fuel consumption	455 g/kWh
Idling speed	2200 rpm
Maximum power speed	7500 rpm
Power output	1.6 kW
Spark plug	NGK CMR7H
EQUIPMENT	
OEM Harness	Integrated
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	104 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) handle	2.2 m/s²
Exhaust emissions (CO average)	536 g/kWh

PXM_SPAREPARTS



AIR FILTER
502 84 44-01



SPARK PLUG
521 23 34-01



502 84 31-01

502 84 35-01



504 11 77-01



506 74 26-01



505 30 67-01



LOWER TUBE
504 06 46-01