

## Datasheet

# RS Pro Double Level Terminal Block, ZRKD series, 2.5mm<sup>2</sup>, 500 V, 24A, Spring Termination, Grey, Double Level

RS Stock No: **763-7438**



## Product Details

RS Pro terminal block in grey colour, has a voltage rating of 500 V and current rating of 24 A. This double level, spring termination terminal block provides safe and quick connections for 2.5 mm<sup>2</sup> solid and stranded wires, with or without wire-end ferrules. The earth terminal features a PE foot contact that is snapped on, ensuring mechanical and electrical safety on both sides of the terminal without screws. The DIN rail terminal meets UL and CSA standards.

## Features and Benefits

- This system provides safe and quick connections for solid and stranded wires, with or without wire-end ferrules.
- The earth terminals feature a PE foot contact that is snapped on, ensuring mechanical and electrical safety on both sides of the terminal without screws.
- Spring termination system

**Specifications:**

Cable CSA	2.5 mm <sup>2</sup>
Colour	Beige
Current Rating	24 A
Maximum Operating Temperature	+120°C
Minimum Operating Temperature	-40°C
Number of Levels	Double
Termination Method	Spring
Voltage Rating	500 V
Wire Size	20 to 12 AWG
Clamping Area	0.08 to 4 mm
Dimensions	83.6 x 5.1 x 53 mm
Material	Nylon 66
Standards Met	UL, CSA