



Small Signal MOSFET Transistor **multicomp** PRO



SOT-23

Features:

- High Density Cell Design For Low $R_{DS(ON)}$
- Voltage Controlled Small Switch
- Rugged and Reliable
- High Saturation Current Capability

Applications:

- N-channel enhancement mode effect transistor
- Switching application.

Maximum Ratings:

$T_A = 25^\circ\text{C}$ unless otherwise specified.

Parameter	Symbol	Value	Units
Drain-Source voltage	V_{DSS}	60	V
Drain-Gate voltage ($R_{GS} \leq 1\text{M}\Omega$)	V_{DGR}	60	V
Gate -Source voltage - continuous Non Repetitive ($t_p < 50\mu\text{s}$)	V_{GSS}	± 20 ± 40	V
Maximum drain current - Continuous - Pulsed	I_D	115 800	mA
Power dissipation	P_D	200	mW
Thermal resistance, junction-to-ambient	$R_{\theta JA}$	625	$^\circ\text{C}/\text{W}$
Junction and storage temperature	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Small Signal MOSFET Transistor **multicomp** PRO

Electrical Characteristics:

T_A = 25°C unless otherwise specified.

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Drain-Source breakdown voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =10μA	60			V
Gate Threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1	2.1	2.5	
Gate-body leakage Forward Reverse	I _{GSS}	V _{DS} =0V, V _{GS} =20V V _{DS} =0V, V _{GS} =-20V			100 -100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} =60V, V _{GS} =0V			1	μA
		V _{DS} =60V, V _{GS} =0V, T _J =125°C			500	
On-state drain current	I _{D(on)}	V _{GS} =10V, V _{DS} ≥ 2V _{DS(on)}	500	2,700		mA
Drain-Source on-voltage	V _{DS(on)}	V _{GS} =10V, I _D =500mA		0.6	3.75	V
		V _{GS} =5V, I _D =50mA		0.09	1.5	
Forward trans conductance	g _{FS}	V _{DS} ≥ 2V _{DS(on)} , I _D =200mA	80	320		mS
Static drain-Source on-resistance	R _{DS(on)}	V _{GS} =10V, I _D =500mA		1.2	7.5	Ω
		V _{GS} =10V, I _D =500mA, T _J =100°C		1.7	13.5	
		V _{GS} =5V, I _D =50mA		1.7	7.5	
		V _{GS} =5V, I _D =50mA, T _J =100°C		2.4	13.5	
Drain-Source diode forward voltage	V _{SD}	V _{GS} =0V, I _D =115mA		0.88	1.5	V
Input capacitance	C _{ISS}	V _{DS} =25V, V _{GS} =0V, f=1MHz		20	50	pF
Output capacitance	C _{OSS}			11	25	
Reverse transfer capacitance	C _{RSS}			4	5	
Turn-On delay time	t _{D(on)}	V _{DD} =30V, I _D = 0.2A, R _L = 150Ω, V _{GS} = 10V, R _{GEN} = 25Ω			20	ns
Turn-Off delay time	t _{D(off)}				20	ns

Typical Characteristics:

T_a=25°C unless otherwise specified.




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Gate Voltage and Drain Current




Figure 3. On-Resistance Variation with Temperature




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Transfer Characteristics




Figure 6. Gate Threshold Variation with Temperature




Figure 7. Breakdown Voltage Variation with Temperature





Figure 8. Body Diode Forward Voltage Variation with Temperature

Small Signal MOSFET Transistor **multicomp** PRO

Package Outline:


Plastic surface mounted package



SOT-23		
Dim.	Min.	Max.
A	2.85	2.95
B	1.25	1.35
C	1 Typ.	
D	0.37	0.43
E	0.35	0.48
G	1.85	1.95
H	0.02	0.1
J	0.1 Typ.	
K	2.35	2.45

Dimensions : Millimetres

Soldering Footprint:



Dimensions : Millimetres

Package Information:

Device	Package	Shipping
2N7002-7-F	SOT-23	3,000 / Tape & Reel

Part Number Table

Description	Part Number
Small Signal MOSFET Transistor	2N7002-7-F

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO