

FEATURES

- Thermally bonded
- G3 grade
- CP413 BS5588 Part 9 approvals

RS PRO Filter Media G3 Grade, 20 x 1m 14mm

RS Stock No.: 122-1771



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

Brought to you by RS PRO this item is a synthetic (100% polyester fibre) filter media supplied in a roll. Thermally bonded by means of bi-component fibres, the filter media is suitable for use as a general pre-filter for HVAC and kitchen hood applications.

Options available:

827-9510 - Filter media roll white 1000mm x 2000mm x 10mm (thickness)

<u>122-1771</u> - Media Roll 1000mm x 20m x 14mm (thickness)

122-1772 - Media Pad 1000mm x 1600mm x 14mm (thickness)

General Specifications

Filter Grade	G3
Initial Pressure Drop	35Pa
Applications	General pre filter for HVAC and kitchen hoods

Mechanical Specifications

Dimensions	20m x 1m
Thickness	14mm
Length	20m
Width	1m

Property		
Recommended Final Pressure Drop	250Pa	
Media Velocity	1.5m/s	
Initial Resistance	77.70%	
Average Arrestance	87.50%	
Dust Holding Capacity	400g/m ²	
Thermal Stability	100°C	



Approvals

Compliance/Certifications	DIN 53438, EN 779, ISO 9073-2
Flammability	K1/F1



