



1000 V. They can withstand impulses in excess of 8,000 V and reduce risks related to surges and spikes.

Other useful features:

- Lifetime warranty
- 6000 counts, 3-3/4 digits
- Measure up to 1000 V AC and DC
- Measure up to 10 A, 20 A for up to 30 seconds
- Built in thermometer lets you carry one less tool (temperature probe included)
- Frequency to 200 kHz and % duty cycle
- Resistance, continuity
- RPM measurements with inductive pickup
- Millisecond pulse width measurements for fuel injectors
- Magnet hanger to attach meter to the vehicle and free your hands for other tasks
- 10,000 µF capacitance range for components and motor caps
- Min/Max-Average recording with Min/Max Alert to capture variations automatically
- Peak capture to record transients as fast as 250 µs
- Relative mode to remove test lead interference from low ohms measurements
- Auto and manual ranging for maximum flexibility
- Touch Hold to capture stable readings avoiding noisy signals
- Large display digits and two-level bright white backlight for increased visibility
- Analog bargraph for fast changing or unstable signals
- Input Alert provides audible warning against wrong use of input jacks
- Improved selectable sleep mode for long battery life
- Access door for fast battery changes without opening up the case
- "Classic" design with new removable holster with built in test lead and probe storage
- 10 meg ohm input impedance wont load circuits
- 0.1% DC accuracy

Position the meter in the most usable location with the magnetic hanger

The holster on the new Fluke 88V accepts a small but extremely powerful magnet (Fluke Tpak) that holds the meter firmly to most steel surfaces. This allows you to focus on taking measurements instead of holding the meter in your hand.

Electrical safety

All inputs are protected to Category III, 1000 V and Category IV 600 V. They can withstand impulses in excess of 8,000 V and reduce risks related to surges

Specifications: Automotive Multimeters: Fluke 88V/A Automotive Multimeter Combo Kit

| Technical Specifications | | |
|--------------------------|-----------------|-------------|
| DCV | Maximum Voltage | 1000 V |
| | Accuracy | ±(0.1% + 1) |
| | Best Resolution | 0.01 mV |

| | | |
|-------------------------|--|-------------------------|
| ACV | Maximum Voltage | 1000 V |
| | Accuracy | $\pm(0.5\% + 2)$ |
| | AC Bandwidth | 5 kHz |
| | Best Resolution | 0.01 mV |
| DC Current | Maximum Amps | 10 A |
| | Amps Accuracy | $\pm(0.4\% + 2)$ |
| | Best Resolution | 0.001 mA |
| AC Current | Maximum Amps | 10 A |
| | Amps Accuracy | $\pm(1.2\% + 2)$ |
| | Best Resolution | 0.001 mA |
| Resistance | Maximum Resistance | 50 M Ω |
| | Accuracy | $\pm(0.4\% + 1)$ |
| | Best Resolution | 0.1 Ω |
| Capacitance | Maximum Capacitance | 9,999 μ F |
| | Accuracy | $\pm(1\% + 2)$ |
| | Best Resolution | 0.01 nF |
| Frequency | Maximum Frequency | 200 KHz |
| | Accuracy | $\pm(0.005\% + 1)$ |
| | Best Resolution | 0.01 Hz |
| Duty Cycle | Maximum Duty Cycle | 99.9% |
| | Accuracy | within 2% per KHz +0.1% |
| | Best Resolution | 0.1% |
| Temperature Measurement | -200.0°C - 1090°C -328.0°F - 1994.0°F, 1.0% excluding probe | |
| 80 BK Temperature Probe | -40°C - 260°C -40°F - 500°F, 2.2°C or 2% whichever is greater | |
| Conductance | Maximum Conductance | 60.00 nS |
| | Accuracy | $\pm(1.0\% + 10)$ |
| | Maximum Resolution | 0.01 nS |
| Operating Range | Operating Temperature | -20°C - 55°C |
| | Storage Temperature | -40°C - 60°C |
| Physical | 5.2 x 9.8 x 20.1 cm (2.06 x 3.86 x 7.93 in) 624 g (22 oz) | |

Ordering information



Fluke 88V/A Kit

Fluke 88V/A Automotive Multimeter Combo Kit

Includes:

- 88V Automotive Multimeter
- TL224 silicone test leads
- AC285 long reach alligator clips
- TP220 test probes
- RPM 80 inductive RPM
- TPAK ToolPak™ Magnetic Meter Hanging Kit
- 80BK temperature probe
- Two automotive backprobe pins
- Insulation piercing probe
- C800 durable carrying case
- Holster
- 9V battery (installed)
- Getting started manual
- CD with detailed manual

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2023 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
05/2023

**Modification of this document is not permitted
without written permission from Fluke Corporation.**