

## FEATURES

- With stainless steel pressure sensor
- Peak value detection (1000 measurements / s)
- Large double display with background illumination
- Waterproof (IP65/IP67)
- Durable with long battery life
- Modern compact housing.
- Calibrated and fully interchangeable pressure probes

## RS MH 5130 + RS MSD 10 BRE

RS Stock No.: 205-0969



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# Manometer

## Product Description

This handheld instrument is a valuable tool for demanding pressure measurements. Extremely robust plug connections, the silicone protection cover, backlight and a waterproof design allow its usage in harsh industrial and field environments.

The supplied stainless steel pressure sensor is suitable for: air, aggressive media, water, etc.

### Application:

- Industry and craft, HVAC: heating, ventilation, air-conditioning
- Leakage test / pressure test
- Measurements of gas and oil firings
- Hydraulic analysis (peak pressure)

## General Specifications

<b>Model Name</b>	<b>RS MH 5130 + RS MSD 10 BRE</b>
<b>Display Range Measuring Instrument</b>	<b>Max. -19999 ... 19999 digit, depends on used sensor</b>
<b>Number of channels</b>	<b>1</b>
<b>Sensor Pressure Range</b>	<b>0...10,00 bar rel.</b>
<b>Sensor Pressure Port Type</b>	<b>Relative</b>
<b>Number of Pressure Ports</b>	<b>1</b>
<b>Selectable Units</b>	<b>mbar / bar / kPa / MPa / inHg / mmHg / psi / mH<sub>2</sub>O</b>
<b>Maximum Overpressure</b>	<b>max 35 bar rel.</b>
<b>Resolution</b>	<b>10 mbar</b>
<b>Response Time</b>	<b>&lt; 1 ms (at measuring rate = peak detection)</b>
<b>Over Range Indicator</b>	<b>Yes</b>
<b>Under Range Indicator</b>	<b>Yes</b>
<b>Zero Pressure Correction</b>	<b>Yes</b>
<b>Accuracy Device</b>	<b>±0.1 % FS</b>
<b>Accuracy Sensor (typ. values)</b>	<b>±0.2 % FS (hysteresis and linearity) ±0.02 % FS/K (TC for zero or slope @ 0..70 °C)</b>
<b>Display Type</b>	<b>4 ½ digit 7-segment, illuminated (white)</b>
<b>Alarm</b>	<b>N/A</b>
<b>Data Logging</b>	<b>No</b>
<b>Leak Testing</b>	<b>Yes</b>
<b>Low Battery Indicator</b>	<b>Yes</b>
<b>Minimum / Maximum Recordings</b>	<b>Yes</b>
<b>Intrinsically Safe</b>	<b>No</b>
<b>Interface</b>	<b>Yes</b>
<b>Calibration Available</b>	<b>Factory calibration protocol for device, Calibration certificate for sensor optionally available</b>

# Manometer

## Electrical Specifications

Battery Type	2 x AAA
Battery Life	500 h
Auto Power Off time	1 ... 120 minutes, can be deactivated
Low Battery Indicator	Yes

## Mechanical Specifications

Housing Material Device	Break-proof ABS housing
Connection Pressure Sensor	1 x 7-pole bayonet connector
Connection Output / external supply	4-pole bayonet connector for serial interface, supply (with accessories: USB adapter USB 5100)
Device Dimensions	160 x 86 x 37 mm (H x W x D) incl. silicone protection cover (red)
Length	160 mm
Width	86 mm
Height	37 mm
Housing Material Sensor	Stainless steel
Connection Device	M12-plug (for connection cable RS MSD-K51)
Pressure connection	Connection thread G1/4", key width: 27 mm
Sensor Dimensions	approx. Ø 30 x 89 mm
Weight	approx. 480 g (device, protection cover, sensor and connection cable)
Vibration Resistance	Not specified
Shock Resistance	Not specified

## Operation Environment Specifications

Relative Humidity	0..95 %RH (non condensing)
Minimum Operating Temperature	-25 °C
Maximum Operating Temperature	+50 °C
Storage Temperature Range	-25 to +70 °C

## Protection Category

IP Protection	IP 65 / IP 67 (device), IP 67 (sensor), IP 54 (sensor plug)
---------------	----------------------------------------------------------------

# Manometer

## Additional Information

Custom Tariff Number	90262020
----------------------	----------

## Approvals

Compliance/Certifications	CE
Declarations	Manufacturer Conformity

## Accessories Includes

Stock #	Item Name	Item Description	Qty
	RS MSD 10 BRE	pressure sensor 0 – 10.00 bar rel.	1
	RS MSD-K51	Connecting cable for RS MSD Sensor to RS MH 5130	1

## Similar Products

Parameters	Stock# 205-0966	Stock# 205-0968	Stock# 205-0967
Model Name	RS MH 5130 + RS MSD 2.5 BAE	RS MH 5130 + RS MSD 10 BAE	RS MH 5130 + RS MSD 350 MR
Sensor Pressure Port Type	Absolute	Absolute	Difference, Relative
Number of Pressure Ports	1	1	2
Pressure Range	0...2,500 bar abs.	0...10,00 bar abs.	0...350,0 mbar rel.
Selectable Units	mbar / bar / kPa / MPa / inHg / mmHg / psi / mH <sub>2</sub> O	mbar / bar / kPa / MPa / inHg / mmHg / psi / mH <sub>2</sub> O	mbar / bar / kPa / inHg / mmHg / psi / mH <sub>2</sub> O
Resolution	1 mbar	10 mbar	0,1 mbar
Response Time	< 1 ms	< 1 ms	< 1 ms
Maximum Overpressure	max 10 bar abs.	max 35 bar abs.	max 1 bar rel.
Accuracy Device	±0.1 % FS		
Accuracy Sensor (typ. values)	±0.2 % FS (hysteresis and linearity) ±0.02 % FS/K (TC for zero or slope @ 0..70 °C)		±0.2 % FS (hyst. and lin.) ±0.4 % FS (TC for zero or slope @ 0..50 °C)
Display Type	4 ½ digit 7-segment, illuminated (white)		
Alarm	No		
Data Logging	No		
Leak Testing	Yes		
Low Battery Indicator	Yes		
Min./ Max. Recordings	Yes		
Intrinsically Safe	No		
Interface	Yes		