

Datasheet

RS Pro Disconnect Terminal Block, TRK 1.5/15 series, 400 V (IEC), 600 V (CSA/UL), 10 A (IEC), 15 A (CSA/UL)

RS Stock No: **501-853**



Product Details

RS Pro disconnect terminal block in brown colour, has a voltage rating of 400 V (IEC), 600 V (CSA/UL) and current rating of 10 A (IEC), 15 A (CSA/UL). This TRK 1.5/15 series disconnect terminal block has lever action for isolation of circuits. It is suitable for use with standard 15 mm symmetrical rail. The disconnect terminal block meets UL, CSA and NEMKO standards.

Features and Benefits

- For use with standard 15mm symmetrical rail
- Earth terminal tightens on with centre screw
- Disconnect has lever action for isolation of circuits
- Screwless end stop simply dips onto rail

**Specifications:**

Cable CSA	0.2 to 4
Colour	Brown
Current Rating	15 A (CSA), 10 A (IEC), 15 A (UL)
Termination Method	Screw
Voltage Rating	600 V (CSA), 400 V (IEC), 600 V (UL)
Wire Size	22 to 12 AWG
Clamping Area	0.2 to 4 mm
Dimensions	38.3 mm x 6 mm x 48 mm (TS 15)
Material	Nylon 66
Screw Size	M3
Standards Met	UL, CSA, NEMKO, IEC