



Benefits

- Robust design and time-tested functionality in extreme weather conditions
- Made of high-impact, marine-grade corrosive-resistant materials and is designed to last
- Long lifespan of 35,000hrs
- Solar-powered with autonomy run time in excess of 2-3 days

Application



| Model | Item Description | W | PF | lm | lm/W | CRI | BA | h | Single Box (LxWxH)mm | Outer Box (LxWxH)mm | Packing Qty (PCS/CTN) |
|--------------------|--|---|-----|-----|------|-----|-----|-------|----------------------|---------------------|-----------------------|
| ZDL1179-2W-CPD0406 | SIGV1 SOLAR GSL CPD0406 3000K 2W IP65 | 2 | 0.9 | 200 | 100 | 80 | 90° | 35000 | / | 170*170*710 | 1 |

Application Conditions

| | |
|-------------------------|----------|
| IP | IP65 |
| Working Temperature | -25~55°C |
| Application Temperature | 25°C |
| Storage Environment | -25~50°C |

Mechanical Properties

| | |
|------------------|----------|
| Optical Material | PC |
| Housing Material | ALU & PC |
| Finishing Colour | Black |

Electrical Supply

| | |
|------------------|---|
| Solar panel | 5V/2W Monocrystalline solar panel Grade A |
| Battery | 3.2V/2000mAh |
| Charging time | 3-5H |
| Discharging time | 2~3 days |

Dimensional Drawing

