

FEATURES

- Can be installed on most internationally-available ball valves to prevent the handle being turned.
- Prevent valve handle from being turned on.
- Non-conductive
- Can be installed in open and closed positions

6mm Shackle Polyurethane Plastic Ball Valve Lockout, 3.17cm Attachment Point

RS Stock No.: 818-8048



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From RS PRO, comes a range of great value and high quality ball valve lockouts. Manufactured to industry standards, these rigid lockout shackles operate by clamping over the ball valve lever to prevent the valve from operating. These lockouts can be installed whether the valve is in the open or closed positions, making these a fantastic lockout solution for safe maintenance and repair of any hazardous machinery or equipment.

General Specifications

| | |
|-----------------|--|
| Type | Ball Valve Lockout |
| Material | Polyurethane Plastic |
| Package | Single unit in PVC clear polythene bag |

Mechanical Specifications

| | |
|--------------------------------------|----------------------|
| Dimensions | 150mm X 76mm X 95 mm |
| Length | 150mm |
| Width | 76mm |
| Height | 95mm |
| Attachment Point Minimum Size | 9.52mm |
| Attachment Point Maximum Size | 3.17cm |
| Lock Shackle Maximum Diameter | 6mm |
| Weight | 160 gm |

Approvals

| | |
|----------------------------------|-------------------------|
| Compliance/Certifications | 2011/65/EU and 2015/863 |
|----------------------------------|-------------------------|

