

## W4 WATER REPELLENT

#### NANO SIZE, INVISIBLE, DEEP PENETRATING IMPREGNATOR

#### USES

- Extensive water repelling of exposed porous stone, granite, marble, roof tiles, concrete roof, cement plaster, brick, gypsum, limestone, terra-cotta, clay tile, precast wall, outdoors stone monuments, historical buildings, temple statue, bridge girder, drain culvert etc.
- Reducing sulphurous gases and acid that penetrate the building material by capillary action. Reducing salt formation & damages.



#### **FEATURES**

- W4 is a water miscible solvent-based micro-emulsion concentrate based on silane / siloxane.
- W4 works by penetration and micro-crystallisation, expanding and filling itself in the pores. At the same time, it allows breathing, so that trapped moisture can escape, reducing salt formation that causes concrete spalling, efflorescence, cracking and fungus growth.
- W4 will impart water droplet effect to the treated surface, reducing water absorption by up to 99%.
- W4 has been giving long-term performance of up to 20 years (with slight yellowing on white marble surfaces). It is not affected by UV and abrasion
- W4 is a good concrete sealer before painting. It seals against alkaline breaching and improves paint adhesion. Extending paint service life by 2 to 3 years. It can also be added into emulsion paint at 1% level before painting. W4 is water

miscible, and is environmentally friendly.

#### **APPLICATION METHOD**

#### Dilution: W4 + Clean Water = 1 + 50 (use it within 24 hours)

- Ensure surface is clean and dry. Use roller or brush.
- Apply 1 to 2 coats wet over wet.
- Application Temperature: 0 ° C to 50 ° C.
- Coverage: About 40- 80 m<sup>2</sup>
- Drying time: 30 minutes at 25 °C.
  - Curing time: 1 day at  $30^{\circ}$ C and 10 days for cold climate.

Stone is sensitive, test apply on a small area, to check on the changes in shade. Before full application.

#### CAUTION

- Avoid naked fame. Do not apply by mist spraying. Use in a well-ventilated area.
- Do not use **W4** to waterproof the bottom surface of the marble and stone tiles as it will lead to debonding.
- Do not allow **W4** to form water patches, as it will dry into dark and oily silicone stain. Stain can be removed by torching it with gas burner and scrubbing, best by polishing or buffing.
- Highly polished light coloured tight grain granite and marble tiles have to be handled with care. Do not over coat to avoid wet looking silicone stain. Silicones Stain can only be removed by polishing.



POROUS SURFACE TREATED WITH W4



# W4 WATER REPELLENT

#### NANO SIZE, INVISIBLE, DEEP PENETRATING IMPREGNATOR

A liquid concentrate with slight pungent smell.

#### **TECHNICAL DATA**

- Form
- Active Content
- Depth of penetration Greater than 4 mm.
- Concrete cup test 99% of water remains in the cup after 24 hours. •
  - Detergent water will leak dry in 30 minutes.
- 12 months. Store below 30 °C. Shelf Life

100 %

- Greater than 25 °C. Flash Point
- PSB tested on Oct 3, 2003. Water Absorption Rate 0.01 % after treatment. Testing

#### REMARKS

- **ORAL EXPOSURE:** In case of ingestion, rinse the mouth with water. Call a physician.
- INHALATION EXPOSURE: In case of inhalation, proceed to an open space. If breathing becomes difficult, call a physician.
- DERMAL EXPOSURE: In case of contact, immediately remove clothing and rinse with copious amounts of water. Call a physician.
- EYE EXPOSURE: In case of contact, immediately rinse with copious amounts of water for at least 15 minutes. Assure adequate rinsing by separating the eyelids. Call a physician.

#### PACKING

100ml-Bottle, 0.5 liter-PE Bottle,

1 liter-PE Bottle, 5 liter-PE Bottle,

20 liter-Jerry Can



Disclaimer: The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.



## W4 WATER REPELLENT

#### NANO SIZE, INVISIBLE, DEEP PENETRATING IMPREGNATOR



HILLVIEW MANSION



Far East Square



MALAYAN RAILWAY 1998



2019-12-30 after 21 years No stain on the ceiling



### The Singapore Environment Council hereby grant

the right to use the Singapore Green Label for

### WARRIOR W4

### 032-136-3551

### "Environmentally Preferred Coating"

(In accordance to SEC Green Label Category 32 : Paint and Surface Coating Version 1)

Validity: 16 September 2019 to 15 September 2020

In Le

JEN TEO Executive Director Singapore Environment Council





1 Kay Siang Road #07-01 S(248922)