1000L New IBC w/composite pallet & with valve



Composite Pallet

- > Better option to all steel pallet
- Block / connectors made of PE rust and corrosion proof
- > Does not get damaged easily with fork lift handling equipment
- Plastic drip pan no rust, longer life
- Easily serviceable
- Earthed for ground contact
- Interstackability is provided for all pallets

| Product Name : Intermediate Bulk Cont | | ainer (IBC) Nominal Capacity : 1000 litre | |
|---------------------------------------|--|---|------------------|
| Tare \ | Weight : 57 kg ± 3kg | MFI Suitable : 6 ~ 7 gms/10 min (21.6kg/19 | O ⁰) |
| Colou | r : Natural | Maximum S.G : 1.9 | |
| Туре | : Composite Pallet | Material : High Density Polyethylene (H | DPE) |
| | INTERME | DIATE BULK CONTAINER (IBC) SPECIFICATION | |
| No. | Item | Specification | |
| 1. | Height | 1165mm ± 10mm | |
| 2. | Width | 1000mm ± 10mm | |
| 3. | Length | 1200mm ±10mm | |
| 4. | Embossing dial | Indicator | |
| 5. | Inner container weight | 15kg ± 0.5kg | |
| 6. | Bottom Lift Test | As per UN standard, Clause 6.5.6.4; Should Pass | |
| 7. | Top Lift Test | As per UN standard, Clause 6.5.6.5; Should Pass | |
| 8. | Stacking Test | As per UN standard, Clause 6.5.6.6; 24 hours at 5000kg | |
| 9. | Leak Proofness Test | As per UN standard, Clause 6.5.6.7; 20kPa for 10 minutes | |
| 10. | Internal Pressure (Hydraulic) Test | As per UN standard, Clause 6.5.6.8; 100kPa for 10 minutes | |
| 11. | Drop Test | As per UN standard, Clause 6.5.6.9; 1.9 metre | |
| 12. | Vibration Test | As per UN standard, Clause 6.5.6.13; 1 hour | - |
| 13. | ESCR Test | As per ASTM 1693; Should Pass | |
| 14. | Minimum wall thickness | 1.5mm | |
| 15. | UN Marking | 31HA1/Y/** SGP/QPI 032/5000/1957 | |
| SER | TO SECURE OF STATE OF | APPLICABLE ACCESSORIES | |
| No. | Item | Specification | |
| 1. | Top filling opening system | Plain, 150 mm | |
| | Recommended torque | 100Nm ~ 120Nm | |
| | Material | Polyethylene (PE) ; Black colour | |
| | Gasket for filling opening material | EPDM | |
| 2. | Valve system | 2" Butterfly Valve with Polyethylene (PE) gasket | |
| 3. | Identification Plate | 2 sides (front & back); standard size, 504mm x 396mm | |
| 4. | Additional features | Security Flap and Elbow Connector are supplied. Camlock adaptor is or | otion |

NOTE:

- . Inner and outer surface shall be smooth and free from defect. IBC shall be clean and neat.
- Specified 'QA Accept' sticker shall be fixed on all online tested and OK products.
- All online tests shall be completed.