


# FLAMETECH

## 2KG · 5KG

### Carbon Dioxide Fire Extinguisher



MODEL	FT02-02F-00	FT02-03D-00
Capacity	2KG	5KG
Extinguishing Agent	Carbon Dioxide	
Test Standard	EN3	
Operation Method	Stored Pressure	
Propellant	Carbon Dioxide	
Cylinder Diameter	103 MM	135.8 MM
Total Height	565 MM	755 MM
Total Weight	6.4 KG	13.5 KG
OperateTemp	-30°C to 60°C	
Working Pressure	56 BAR	
Test Pressure	250 BAR	
Fire Rating	34B	89B
Pack Dimension(mm)	125x160x600 (1per box)	145x180x775 (1per box)
PART NO		



EN3

Wheelmark

#### Information

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

Effective against **electric fires**. Note that before attempting to fight electric fires, the electricity must be turned off.

Carbon dioxide is a **clean agent** that leaves no residue upon discharge.

#### Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.


## Accessories



Universal Bracket



Marine Bracket



(Default)

L Bracket

Due to constant improvements, product dimensions may differ slightly.