



Main

Range	Vivace
Product or component type	Switch
Device short name	KB34
Device application	Lighting
Switch function	1-way

Complementary

Device presentation	Complete mechanism
Actuator	Rocker
Number of gangs	4 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	35 mm
Rated current	16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	COM L1 L2
Tightening torque	0.4 N.m
Clamping connection capacity	$\leq 2.5 \text{ mm}^2$
Width	146 mm
Height	86 mm

Environment

Standards	IEC 60669-1 SS 227 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	8.6 cm
Package 1 Length	14.6 cm
Package 1 Weight	150 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	21 cm
Package 2 Width	31.5 cm
Package 2 Length	50 cm
Package 2 Weight	7500 g
Unit Type of Package 3	P12
Number of Units in Package 3	1000
Package 3 Height	120 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	222000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile