

Safety Data Sheet

pro-POWER

1. Information about the goods and manufacturer:

Name of Goods: Dual Wall Flame-retardant Heat Shrink Tubing (P/N HS400-HS412)
Description of Goods: Irradiated Polyolefin Heat Shrink Tubing with meltable adhesive liner
Name of Manufacturer or Supplier of the goods: Premier Farnell plc 150 Armley Road Leeds LS12 2QQ +44 (0) 870 129 8608

2. Chemical Properties:

Ingredient	Chemical Formula	Function	Percentage	CAS No.
Polyolefin	$(CH_2CH_2)_n$	Main Material	50%	9002-88-4
Magnesium hydroxide	$Mg(OH)_2$	Flame Retardants	30%	1309-42-8
APP	—	Flame Retardants	10%	7723-14-0
Pigment	Pigment	Colorant	5%	83524-75-8
Ho-melt Adhesive	EVA	Sealant	5%	-

3. Hazard Information

Key Hazards	Toxicological Effects on Health: After the tubes are ignited, the flame will self-extinguish in a short time. A little fume will give off and have slight harm on the respiratory passage of the human body.
	Influence on Environment: It will cause air pollution when the tubes burn.
	Physical and Chemical Hazards: Normally it is in tubular shape, and shrink at 70-125°C, which perhaps is harmful.
	Special Hazards: When roasted or fumigated, the smoke given off will have impact on the eyes and respiratory system, and is harmful to the human body.

Safety Data Sheet

pro-POWER

Main symptoms: Weep, sneeze, cough, etc. These symptoms can be relieved through breathing fresh air.

Hazards generated when burning : The tubing will burn for a short period of time after being ignited.

4. First-Aid Measures:

First-aid measures for exposing in different occasions:

Inhalation: During proper operation, there is no danger caused by inhalation.

Skin contact: No damage to skin in normal contact. As skin is easily scratched by the tubes, the operators are suggested to put on gloves in operation.

Eye contact: No harm.

Ingestion: Not edible

Key harmful effects: It will impact the respiratory System if you inhale smokes generated by the burning of the tubes.

Protective measures for the rescuers: Wear respiration protection equipment.

Suggestions to doctor: Those who have suffered severe damage in respiratory system should keep on inhaling fresh air to relieve the symptom. j\

5. Fire-fighting Measures

Suitable fire-extinguishing agent: Dry Powder Extinguisher should be used in order to put out the fire in a short time.

Special harms possibly incurred in fire-fighting: Small amount of smoke will give off when the tubes burn, which will impact the respiratory system of human body.

Special fire-fighting procedures: No

Special protective equipment for the fire-fighters: Normal fire-extinguishing equipment.

6. Emergency measures for leakage

Attentions need to be paid by individuals: No

Environmental notice: No

Cleaning Method: No

7. Operation and Storage

Operation: The tubes will shrink when heated by oven or heat gun.

Storage: Pack the tubes with cartons properly and place them at a shady place and at normal temperature.

8. Contact controls and personal protection:

Contact controls: Not harmful

Personal protective measures: No

9. Physical and Chemical Properties :

Outer Jacket

	Properties	Test Method	Test result
Physical Properties	Tensile strength /MPa	ASTM D2671	≥10.4
	Elongation/%	ASTM D2671	≥300
	Tensile strength after aging/MPa	UL 224: 158°C ×168hr	≥7.3
	Elongation after aging/%	UL 224: 158°C ×168hr	≥200
	Heat Resistance	UL 224: 250°C×4hr	No viscosity No Cracking
	Cold blend	UL 224: -30°C×4hr	No Cracking
Electrical Properties	Dielectric Strength(KV/mm)	IEC243	≥20
	Volume resistance/Ω·cm	IEC93	≥1×10 ¹⁴
Chemical Properties	Anti Corrosion	UL 224 158°C×168hr	PASS
	Copper stability	UL 224 158°C×168hr	PASS
	Flammability	UL 224	VW-1
	Water Absorption %	ASTM-D570	≤0.5

Hot-melt adhesive

Property	Test Method	Test result
Water Absorption	ASTM D570	≤0.2
Softening Point	ASTM E28	95°C
Peel Strength (PE)	ASTM D1000	120N/25mm
Peel Strength (AL)	ASTM D1000	80N/25mm

10. Stability and Reactivity of the goods:

Stability: irresolvable
Hazardous effects under special conditions: If exposed to fire, the products will burn in a short time and give off smoke.
Conditions to be avoided: The products will shrink under high temperature.
Substance to be avoided: Fire
Hazardous decomposition product: Smoke

Safety Data Sheet



11. Toxicological Information

Acute Toxicity: No
Partial Effect: No
Allergic Reactions: No
Slow toxicity or long-term toxicity: No
Special Effects: No

12. Ecological Information:

Possible effects on environment: The products are irremediably naturally and are not harmful to animals, plants and aquatic life.

13. Waste Disposal:

Trash disposal: It is suggested that the waste be collected to waste-collection station for treatment.

14. Transport Information

Regulations on international transportation: No
U.N. code: No
Regulations on Domestic transportation: No
Special transportation method and notice: Avoid distortion caused by extrusion and damage caused by edged tools.

15. Regulation Information

Applicable regulation: UL224

Part Number
HS400
HS401
HS402
HS403
HS404
HS405
HS406
HS407
HS408
HS409
HS410
HS411
HS412

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of Premier Farnell Limited 2019.