# NSYBHS500

# Horizontal bar support up to 3200 A 500 mm



Main		
Range	Spacial	
Accessory / separate part category	Busbar accessory	
Product or component type	Busbar support	
Anwendung	Multi-purpose Prisma application	
Enclosure nominal dimensions	-	
Mounting location	On structure of enclosure	
Mounting support	Vertical uprights	
Busbar position	Horizontal	
Range compatibility	Spacial SF Linergy BS Spacial SFP Prisma PH Spacial SFX	

### Complementary

Cubicle-device connection	Linergy BS horizontal busbar - fixed	
Device composition	Fixing elements 1 metal support 2 insulating bar support	
Quantity per set	Set of 1	
Material	Bar support: plastic Metal support: steel	
Fixing mode	By fixing element	
Height	59.25 mm	
Width	410 mm fixing centers:	
Depth	39 mm	
[In] rated current	3200 A	

## **Packing Units**

) kg

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

#### Contractual warranty

Warranty	18 months