

**SCHEDA TECNICA**

Technical data sheet
Fiche technique
Technisches Datenblatt
Ficha técnica

04/05/21

**50MM PANEL MOUNT
MULTI-EFFECT LED
BEACON & BUZZER****RS: 2222439, 2222440****Buzzer piezoelettrico con luce a led multifunzione.***Multi-function piezoelectric sounder with LED light.**Buzzer piézoélectrique multifonctionnel à LED.**Multifunktionaler piezoelektrischer Schallgeber mit LED-Licht.**Sirena piezoeléctrica multifunción con luz LED.*

| | | | | | | | |
|---|--|---|--|--|--------------|---|---|
| CUPOLA DOME DOME HAUBE CÚPULA | PC Opaline | | | | | | |
| CORPO BODY CORPS KÖRPER CUERPO | PC | | | | | | |
| GHIERA RING RING ZWINGE CONTERA | PC | | | | | | |
| GUARNIZIONE SEAL SEAL DICHTUNG EMPAQUETADURA | EPDM | | | | | | |
| CONNETTORE CONNECTOR CONNECTEUR VERBINDER CONECTOR | PRESSACAVO CABLE GLAND PRESSE-ÉTOUPE KABELVERSCHRAUBUNG PRENSAESTOPAS | | | | | | |
| GRUPPO OTTICO OPTICAL GROUP GROUPE OPTIQUE LICHTQUELLE FUENTE DE LUZ | 6 LED SMD | | | | | | |
| RESA LUMINOSA LIGHT OUTPUT RENDEMENT LUMINEUX LICHTEFFIZIENZ EFICACIA LUMINOSA | <table border="1"><tr><td></td><td></td><td></td></tr><tr><td>Cd(p)</td><td>2</td><td>3</td></tr></table> | | | | Cd(p) | 2 | 3 |
| | | | | | | | |
| Cd(p) | 2 | 3 | | | | | |

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.

These data are disclosed for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.

Les données sont divulguées à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis

**SCHEDA TECNICA**

Technical data sheet
Fiche technique
Technisches Datenblatt
Ficha técnica

04/05/21

| TENSIONE DI ALIMENTAZIONE VOLTAGE TENSION SPANNUNG TENSIÓN | 12/24 Vac/Vdc $\pm 10\%$ | | | | | | | | | | |
|--|--|--------|--------|--------|--------|--------|----|----|----|----|-----|
| SERVIZIO SERVICE SERVICE BETRIEBSART FUNCIONAMIENTO | ∞ | | | | | | | | | | |
| CORRENTE NOMINALE CURRENT CONSOMMATION DE COURANT STROMAUFNAHME CONSUMO DE CORRIENTE | <table border="1"><thead><tr><th></th><th>12 Vdc</th><th>24 Vdc</th><th>12 Vac</th><th>24 Vac</th></tr></thead><tbody><tr><th>mA</th><td>45</td><td>45</td><td>90</td><td>110</td></tr></tbody></table> | | 12 Vdc | 24 Vdc | 12 Vac | 24 Vac | mA | 45 | 45 | 90 | 110 |
| | 12 Vdc | 24 Vdc | 12 Vac | 24 Vac | | | | | | | |
| mA | 45 | 45 | 90 | 110 | | | | | | | |
| EFFETTI SONORI/LUMINOSI SOUND/LIGHT EFFECTS EFFETS ACOUSTIQUE/LUMINEUX SOUND / LICHT-EFFEKTE EFECTOS DE SONIDO / LUZ | Luce fissa / Suono continuo / Luce fissa + Suono continuo / 2 Flash sync (60Fpm) / 3 Flash sync (40Fpm) / Intermittente (300Fpm) / Random Steady light / Continuous sound / Steady light + Continuous sound / 2 Flashes sync / 3 Flashes sync / Intermittent / Random Lumière fixe / Son continu / Lumière fixe + Son continu / 2 Flash sync / 3 Flash sync / Pulsé / Random Dauerlicht / Dauerlicht / Dauerlicht + Dauerlicht / 2 Blitzsynchronisation / 3 Blitzsynchronisation / Intermittierend / Zufällig Luz fija / Sonido continuo / Luz fija + Sonido continuo / Sincronización de 2 parpadeos / Sincronización de 3 parpadeos / Intermitente / Aleatorio | | | | | | | | | | |
| GRADO IP IP RATING DEGRE IP SCHUTZART GRADO IP | IP65 | | | | | | | | | | |
| TEMPERATURA DI FUNZIONAMENTO OPERATING TEMPERATURE TEMPERATURE DE SERVICE BETRIEBSTEMPERATUR TEMPERATURA DE FUNCIONAMIENTO | -30°C+50°C | | | | | | | | | | |
| VIBRAZIONI VIBRATIONS VIBRATIONS VIBRATIONEN VIBRACIONES | CEI 60068-2-6 SINE | | | | | | | | | | |
| CERTIFICAZIONI, OMOLOGAZIONI CERTIFICATIONS, APPROVALS CERTIFICATIONS, HOMOLOGATIONS PRODUKTZERTIFIKATE, ZULASSUNGEN CERTIFICADOS, HOMOLOGACIONES | CE | | | | | | | | | | |
| FISSAGGIO MOUNTING FIXATION FIXIERUNG FIJACIÓN | Ghiera Ring Ring Zwinge Contera | | | | | | | | | | |
| DISEGNO TECHNICAL DRAWING DESSIN TECHNISCHE ZEICHNUNG DIBUJO TECNICO | <p>The technical drawing shows a side view of the device with the following dimensions: a top diameter of 26.5, a total height of 86.5, a mounting hole diameter of M22, a base diameter of 40, and a total length of 300. A note indicates a minimum length of 2 and a maximum length of 15 for a specific part.</p> | | | | | | | | | | |

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.

These data are disclosed for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.

Les données sont divulguées à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis