

### **FEATURES**

- Material: UL approved Nylon 66, 94V-2
- Color: Grey (RAL7001)available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.

# **RS PRO Cable Gland**

**RS Stock No.:** 214-1081



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### **Product Description**

- Material: UL approved Nylon 66, 94V-2
- · Color: Grey(RAL7001), available in other colors.
- · Suit a variety of applications, and diverse industries.
- Function: Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.
- Feature: Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number, L for locknut, W for washer, B for gland body, S for seal, N for nut.

#### **General Specifications**

Series	Metric Thread
Туре	Cable Gland
Colour	Grey(RAL7001)
Material	Nylon 66
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	5pcs

#### **Mechanical Specifications**

Thread	PG-48
Mounting Hole	59.3~59.7 mm
Cable Range	34~44 mm

#### **Protection Category**

IP Rating	IP68 (only if the locknut and washer are assembled)
-----------	---



## **Approvals**

Declarations	
Standards Met	UL, RoHS, CE, HF

## **Similar Products**







RS Article	Thread	Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141081	PG-48	59.3~59.7	59	43	46	17	43	31	34 ~ 44	5PCS

\*\* IP68 (only if the locknut and washer are assembled)

