



F1000 FLEXI CLEAR

WATER BASED GLOSS OR MATT SEALER FOR OUTDOOR OR INDOOR USE.

Uses

1. Primer for chalky cement surface.
2. Clear Sealer for Car Park, Slate, Limestone, Cement tile, Earthen Ware, Tile and Porous Surfaces.
3. Metal protection.



Application

1. Surface to be coated has to be clean and dry for maximum absorption. It is better to seal the surface with W4 Water repellent for better paint bonding and durability.
2. Dilute **F1000 FLEXI CLEAR** with suitable amount of water before applying by brush or rollers. Do not apply in 1 heavy coat; it may result in white patch.

Remarks

Not suitable for coating over Red Brick's wall. Due to moisture being trapped has no escape passage but to force out from the coating, resulting in blistering and white patchy stains.

Typical Properties

Type of Copolymer	Acrylic Copolymer, Non Yellowing.
Appearance	Milky blue-white emulsion
Solid	25.0 ~ 27.0%
pH	7.0 ~ 8.0
Glass Transition Temperature	40 °C
Minimum Film Forming Temperature	24 °C
Finishes	Gloss or Matt.
Drying time	30 minutes
Re-coating time	60 minutes
Coverage	4 to 5 m² / kg



F1000 FLEXI CLEAR

WATER BASED GLOSS OR MATT SEALER FOR OUTDOOR OR INDOOR USE.

Storage

F 1000 should be stored in closed containers at temperature between +5°C and +35°C for no more than 6 months and protected from frost and direct sunlight.

Packing

1 kg-bottle, 5 kg-carboy, 20 kg-pail

Personal Precaution

1. Allow used paint in the can to dry up before disposal, to avoid polluting the waterways.
2. In case of skin contact, flush it with water.

Disclaimer: The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.