



#### PRODUCT DESCRIPTION

**REXCO 50 MULTIPURPOSE LUBRICANT** is an excellent multi purpose lubricating product that provides rust resistance over a long period of time to improve equipment performance and protector of metal objects from the oxidation process which cause rust or corrosion. **REXCO 50 MULTIPURPOSE LUBRICANT** is able to lubricate metals that rubs against each other even under heavy load and heat, it will reduce the creaking sound and slow down the metal from wear out quickly.

**REXCO 50 MULTIPURPOSE LUBRICANT** has a strong penetrating power and works quickly to penetrate even the deepest layers, with a quick penetration **REXCO 50 MULTIPURPOSE LUBRICANT** is very effective for cleaning: stains, oil, grease, dust, asphalt that sticks to the surface (Metal, Aluminium, Chrome and painted metal objects does not damage the paint).

#### PRODUCTS



120 ML    220 ML    350 ML    500 ML    3,8 L

#### PRODUCT APPLICATIONS

- Industrial Machines
- Refinery Pipe
- Marine
- Automotive
- Household
- Workshops
- Hobbies
- Components

#### ADVANTAGES & FEATURES

- **REXCO 50 MULTIPURPOSE LUBRICANT** Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- **REXCO 50 MULTIPURPOSE LUBRICANT** Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- Loosens rusty parts.
- Protects from oxidation & corrosion.
- Removes moisture.
- Eliminates squeaks.
- Cleans & removes oil, asphalt & dust.
- High performance lubrication.
- Protects metal surfaces from rust for longer time.
- Chlorine free.

#### DIRECTIONS FOR USE

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application.
- Hold the can and apply from a distance of 15-20 cm. Apply the components thoroughly and paying particular attention to the seized contact areas.
- In same severe cases, apply **REXCO 50 Multipurpose Lubricant** for second time after several minutes may be beneficial.
- Use 360° valve, can be sprayed in any direction.
- Save to use on fabric, plastic, paint, and other finishes.
- **CAUTIONS** : Pressurized container, protect from sunlight, do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Do not breathe spray. Avoid contact with the skin.
- **KEEP OUT OF THE REACH OF CHILDEN.** Contains distillates (petroleum), hydro treated light.

#### TECHNICAL DATA TEST

PARAMETERS	UNITS	TYPICAL DATA	METHODS
Appearance	-	Yellow Transparent	Visual
Odour	-	Mild Smelling	-
Solubility In Water	-	Not Soluble	-
Specific Gravity At 27 °c	-	0.9578	Astm D4052-11
Color Astm	No. Astm	L 3.0	Astm D1500-12
Kinematic Viscosity At 27 °c	Cst	3.108	Astm D445-14
Boiling Point	°c	193	Astm D1120-11
PH	-	5.40	Potentiometric
Flash Point COC	°c	68	Astm D92-12