

Fast-Acting Cartridge Fuses

5mm × 20mm

multicomp PRO

**RoHS
Compliant**



Description

The fast-acting fuse with low breaking capacity for use with printed circuit boards is used in a large variety of applications. This Ø5mm × 20mm device is constructed of a glass tube with electro-plated brass end caps. It is with 250V AC rating and 100 Ampere breaking capacity, offers excellent quality and is 100% tested for cold resistance and precise length.

The fast-acting fuse is ideal for supplementary protection in electrical appliances and equipment to provide excellent protection for components or circuits.

Features

- Miniature fuse with fast-acting, low breaking capacity
- Ø5mm × 20mm physical dimensions
- Glass tube, encapsulated design with nickel - plated brass end caps
- Protection against harmful over-currents in primary and secondary applications
- Lead-free and Halogen-free
- Designed compliant to IEC 60127-2/II

Specifications

Operating Temperature : -55°C to +125°C
 Stock Temperature : +10°C to +60°C
 Relative humidity: ≤75% yearly average without dew, maximum 30 days at 95%
 Vibration Resistance : 24 cycles at 15 min. each (60068-6)
 10-60Hz at 0.75mm amplitude
 60-2000Hz at 10g acceleration

Electrical Characteristics


Time vs Current Characteristics Table

(measured with constant current power supply)

Time vs Current Characteristics			
Rated current	150%	210%	275%
0.25A~6.3A	>1h	<30min	50ms~2s
8A~10A	>1h	<30min	50ms~2s
12.5A~16A	>30min	<30min	50ms~3s

Time vs Current Characteristics		
Rated current	400%	1000%
0.25A~6.3A	10ms~300ms	≤20ms
8A~10A	10ms~400ms	≤40ms
12.5A~16A	10ms~600ms	≤80ms

Average Time Current (I-T) Curves



Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 sg.element14.com/b/multicomp-pro

multicomp PRO

Fast-Acting Cartridge Fuses

5mm × 20mm



Electrical Characteristics at 25°C


Amp Code	Rated Current	Rated Voltage DC	Max. Voltage Drop (mV)	Max. Power Dissipation (W)	Typ. Cold Resistance (mΩ)	Nominal Melting I ² t(A ² sec)	Breaking Capacity
0315	0.315A	125V AC 250V AC	1300	1.6	860	0.109	10KA/125V AC 100A/250V AC
1100	1A		200	1.6	101	1.64	
1200	2A		170	1.6	40.65	5.76	
1500	5A		130	2.5	13.5	41	
1800	8A		130	4	7.5	164	
2100	10A		130	4	6.3	272	
2150	15A		100	6	3.2	980	

Note:

- (1) Permissible continuous operating current is 100% at ambient temperature of 23°C (73.4°F)
- (2) The cURus certification by 125V and 250V; the VDE certification with 8A~10A by 125V and 250V; the others certification by 250V.
- (3) The current values used for calculating I²T should be within the standard range of 8ms ~ 10ms.


Temperature Derating Curve

Temperature Derating Curve



$$\text{Calculation for ideal fuse selection} = \frac{\text{Operating Current (A)}}{\text{Rating (\%}\times 0.75)}$$

Soldering Parameters



- 260°C ≤ 5 sec (Wave Soldering)
- 350°C ≤ 3 sec (Hand Soldering)
- Soldering Peak:
- 260°C - 10 sec (IEC 60068-20)




Fast-Acting Cartridge Fuses


5mm × 20mm



Construction



Diagram



Part Number Table

Description	Part Number
Fast-Acting Miniature Cartridge Fuse, 0.315A, 250V AC, 5mm × 20mm	MP007113
Fast-Acting Miniature Cartridge Fuse, 1A, 250V AC, 5mm × 20mm	MP007114
Fast-Acting Miniature Cartridge Fuse, 1A, 250V AC, 5mm × 20mm	MP006250
Fast-Acting Miniature Cartridge Fuse, 2A, 250V AC, 5mm × 20mm	MP006246
Fast-Acting Miniature Cartridge Fuse, 5A, 250V AC, 5mm × 20mm	MP007115
Fast-Acting Miniature Cartridge Fuse, 8A, 250V AC, 5mm × 20mm	MP007116
Fast-Acting Miniature Cartridge Fuse, 10A, 250V AC, 5mm × 20mm	MP007117
Fast-Acting Miniature Cartridge Fuse, 15A, 250V AC, 5mm × 20mm	MP007118

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 sg.element14.com/b/multicomp-pro

